



Product: <u>1696A</u> ☑

Digital Audio Cable, 1 Pr #22, Str TC, Foil + Braid, PVC Jkt

Product Description

Digital Audio Cable, 1 Pair 22 AWG (7 x 30) Tinned Copper, Datalene® Insulation, Overall Beldfoil® Shield, 90% Tinned Copper Braid Shield, PVC jacket

Technical Specifications

Product Overview

Suitable	Applications:	Digital a	audio. Interconnect bet	ween audio equipment suc	h as micr	icrophor	ones, speal	akers, ampl	ifiers, mixing	consoles	
		Digitare			as mor			anoro, umpi			
Constr	uction Details										
Conducto	r										
Element	No. of Elements Size	Stranding	Material								
Pair(s)	1 22 AWG	7x30	TC - Tinned Copper								
Insulatior											
Element	Material	Nom. Thickr	ness Nom. Insulatio	n Diameter Color Code	Notes	s					
Pair(s)	PE - Polyethylene (Foam)	0.027 in (0.69	mm) 0.082 in (2.1 m	m) Blue & White	HDPE	E					
Outer Shi	eld										
Shield T	vpe Material	Coverage	Drainwire Type								
Таре	Bi-Laminate (Alum+Poly	y) 100%	24 AWG (7x32) TC								
Braid	Tinned Copper (TC)	90%									
_											
Outer Jac	ket										
Material Nom. Thickness Nom. Diameter											
PVC - Polyvinyl Chloride 0.025 in (0.64 mm) 0.235 in (5.97 mm)											
Overall Cable Diameter (Nominal): 0.235 in (5.97 mm)											
			. ,								

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
Pair(s)	18.2 Ohm/1000ft	13 pF/ft (43 pF/m)	26 pF/ft (85 pF/m)	110 Ohm	76%	6 Amps per conductor @ 30°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
60°C	-30°C to +60°C

Bend Radius

Stationary Min. Installation Min.

2.4 in (61 mm) 2.4 in (61 mm)	
Max. Pull Tension:	23.7 lbs (10.8 kg)
Bulk Cable Weight:	31 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	AES/EBU

Product Notes

Notes:	Cabling has two rod fillers for improved electrical performance.		
History			
Update and Revision:	Revision Number: 0.476 Revision Date: 12-22-2023		

Part Numbers

Variants ltem # Color Putup Type Length UPC Footnot 1696A B59250 Black, Matte Reel 250 ft 612825121329 1696A B59500 Black, Matte Reel 500 ft 612825121336 1696A B591000 1,000 ft 612825121312 C Black, Matte Reel 1696A B59U1000 Black, Matte Reel 1,000 ft 612825121305

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.