



Product: [9305](#)

Audio, Control & Instrument, #22-4pr, PVC, O/A Foil, PVC Jkt, CMG

Product Description

Audio, Control & Instrument Cable, 22 AWG solid tinned copper conductors, PVC insulation, 4 twisted pairs, overall Beldfoil® shield (100% coverage), 22 AWG stranded tinned copper drain wire, PVC jacket.

Technical Specifications

Product Overview

|                        |                                                                                                                                                 |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|

Construction Details

Conductor

| Element | No. of Elements | Size | Stranding | Material           |
|---------|-----------------|------|-----------|--------------------|
| Pair(s) | 4               | 22   | Solid     | TC - Tinned Copper |

Insulation

| Material                 | Nom. Thickness     | Nom. Insulation Diameter | Color Code                                              |
|--------------------------|--------------------|--------------------------|---------------------------------------------------------|
| PVC - Polyvinyl Chloride | 0.011 in (0.28 mm) | 0.051 in (1.3 mm)        | Black & Red, Black & White, Black & Green, Black & Blue |

Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 22 AWG (7x30) TC |

Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.032 in (0.81 mm) | 0.265 in (6.73 mm) |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                    |
|--------------------|-------------------------------|-------------------------------------------------|---------------------------------|
| 20.6 Ohm/1000ft    | 35 pF/ft (110 pF/m)           | 50 pF/ft (160 pF/m)                             | 2.03 Amps per Conductor at 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V             |

Mechanical Characteristics

Temperature

| UL Temperature | Operating      |
|----------------|----------------|
| 80°C           | -20°C To +80°C |

Bend Radius

| Stationary Min.   | Installation Min. |
|-------------------|-------------------|
| 2.65 in (67.3 mm) | 2.65 in (67.3 mm) |

|                    |                    |
|--------------------|--------------------|
| Max. Pull Tension: | 62.4 lbs (28.3 kg) |
|--------------------|--------------------|

|                    |               |
|--------------------|---------------|
| Bulk Cable Weight: | 41 lbs/1000ft |
|--------------------|---------------|

Standards and Compliance

|                                  |                                                                              |
|----------------------------------|------------------------------------------------------------------------------|
| Flammability / Reaction to Fire: | UL1685 FT4 Loading, FT4, IEC 60332-1-2                                       |
| CPR Compliance:                  | CPR Euroclass: Eca                                                           |
| NEC / UL Compliance:             | Article 800, CMG                                                             |
| AWM Compliance:                  | AWM 2464                                                                     |
| CEC / C(UL) Compliance:          | CMG                                                                          |
| European Directive Compliance:   | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark                                                                    |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)                                              |

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.437 Revision Date: 12-22-2023 |
|----------------------|--------------------------------------------------|

Part Numbers

Variants

| Item #        | Color  | Putup Type | Length   | UPC          | Footnote |
|---------------|--------|------------|----------|--------------|----------|
| 9305 060100   | Chrome | Reel       | 100 ft   | 612825227397 |          |
| 9305 060500   | Chrome | Reel       | 500 ft   | 612825227410 | C        |
| 9305 060U500  | Chrome | UnReel     | 500 ft   | 612825227380 |          |
| 9305 0601000  | Chrome | Reel       | 1,000 ft | 612825227403 |          |
| 9305 060U1000 | Chrome | UnReel     | 1,000 ft | 612825227373 |          |
| 9305 0605000  | Chrome | Reel       | 5,000 ft | 612825227427 | C        |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.