



**Product:** [543945](#)

Surveillance CCTV, RG-59 #20 BC, 90% BC Braid, CMG

**Product Description**  
Surveillance & CCTV Cable, RG59, Rated-CMG, 20 AWG solid bare copper, foam polyolefin core, 90% bare copper braid, PVC jacket

**Technical Specifications**

**Product Overview**

Suitable Applications:	Surveillance, CCTV Camera
------------------------	---------------------------

**Construction Details**

RG Type:	59
Series Type:	59

**Conductor**

Element	No. of Elements	Size	Stranding	Nom. Diameter	Material
Coax(es)	1	20 AWG	Solid	0.032 in	BC - Bare Copper

**Insulation**

Element	Material	Nom. Insulation Diameter	Color Code
Coax(es)	PE - Polyethylene (Foam)	0.145 in (3.68 mm)	White

Table Notes:	Gas Injected
--------------	--------------

**Outer Shield**

Outer Shield Type	Material	Coverage
Braid	Bare Copper (BC)	90%

**Outer Jacket**

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.232 in (5.89 mm)

Overall Cable Diameter (Nominal):	0.232 in (5.89 mm)
-----------------------------------	--------------------

**Electrical Characteristics**

**Attenuation**

Frequency	Nom. Attenuation	Max. Attenuation
1 MHz	0.3 dB/100ft	0.75 dB/100ft
5 MHz	0.65 dB/100ft	2.15 dB/100ft
10 MHz	0.9 dB/100ft	
50 MHz	1.9 dB/100ft	
100 MHz	2.6 dB/100ft	
200 MHz	3.6 dB/100ft	
400 MHz	5 dB/100ft	
700 MHz	7 dB/100ft	
900 MHz	8 dB/100ft	
1000 MHz	8.5 dB/100ft	

**Electricals**

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.	Max. Delay Skew
11.3 Ohm/1000ft	3.3 Ohm/1000ft (11 Ohm/km)	16.3 pF/ft (53.5 pF/m)	75 Ohm	83%	83 ns/100m

Voltage

UL Voltage Rating
300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-30°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
2.32 in (58.9 mm)	2.32 in (58.9 mm)

Max. Pull Tension:	57 lbs (26 kg)
Bulk Cable Weight:	29 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor, Indoor, Aerial - Black only, When supported by messenger wire
Flammability / Reaction to Fire:	UL1685 FT4 loading , FT4, IEEE 1202 Vertical Tray Flame Test, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMG
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	643948

History

Update and Revision:	Revision Number: 0.593 Revision Date: 05-10-2024
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
543945 010500	Black	Reel	500 ft	612825162476	C
543945 010U500	Black	UnReel	500 ft	612825162469	
543945 0101000	Black	Reel	1,000 ft	612825337089	C
543945 010U1000	Black	UnReel	1,000 ft	612825162452	
543945 009500	White	Reel	500 ft	612825162445	
543945 009U500	White	UnReel	500 ft	612825162421	
543945 0091000	White	Reel	1,000 ft	612825162438	C
543945 009U1000	White	UnReel	1,000 ft	612825162414	

© 2025 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.