



Product: <u>1348A</u> ☑

CC Link, 3 C #20 Str BC, FPE Ins, OS+TC Brd, PVC Jkt, CM

Request Sample

Product Description

CC Link, 3 Conductor 20AWG (7x28) Bare Copper, FPE Insulation, Overall Beldfoil®+Tinned Copper Braid(78%) Shield, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications: harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	3	20 AWG	7x28	BC - Bare Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code	Notes
Conductor(s)	PE - Polyethylene (Foam)	0.028 in (0.71 mm)	0.094 in (2.4 mm)	Blue, Yellow, White	HDPE

Outer Shield

	Shield Type	Material	Coverage	Drainwire Type
ľ	Таре	Bi-Laminate (Alum+Poly)	100%	22 AWG (19x34) TC
ľ	Braid	Tinned Copper (TC)	78%	

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
Р	PVC - Polyvinyl Chloride	0.035 in (0.89 mm)	0.303 in (7.70 mm)
С	Overall Cable Diameter (I	Nominal): 0.303 in (7.70 mm)

Electrical Characteristics

Electricals

	Element	Nom. Conductor DC	CR Nom. Capacitance Cond-to-Cond	Nom. Characteristic Impedence
	Conductor(s)	11.5 Ohm/1000ft	18.3 pF/ft (60.0 pF/m)	110 Ohm
Ī	Nom. Outer S	hield DCR:	3.2 Ohm/1000ft (10 Ohm/km)	

High Frequency

Element	Frequency [MHz]
Conductor(s)	1
	5

Voltage



Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-30°C to +75°C

Bend Radius

Stationary Min.	Installation Min.	
4 in (100 mm)	4 in (100 mm)	

Max. Pull Tension:	86 lbs (39 kg)
Bulk Cable Weight:	49 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1685 UL Loading
NEC / UL Compliance:	Article 800, CM, CL2
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Mitsubishi #BA1SJ61-S, Cable contains fillers

History

Update and Revision:	Revision Number: 0.513 Revision Date: 02-03-2025
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
1348A 0021000	Red	Reel	1,000 ft	612825112365	С
1348A 0025000	Red	Reel	5,000 ft	612825112372	CZ

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.