



**Product:** <u>1312A</u> ☑

Speaker Cable, 4 C #12 Str BC-OFHC, PVC Jkt, CM, DIR BUR, Flexible

# **Product Description**

Speaker Cable, 4 Conductor 12 AWG (168 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

# **Technical Specifications**

Suitable Applicat	tions:	Speake	r Cable; Dir	ect Burial; Indoor/Outdoor H	ome Theater; In-Wall Sp
onstruction	n Details				
onductor					
	o. of Elements	Size	Stranding	Material	
Conductor(s) 4		12 AWG	168x34	BC - Bare Copper (High Co	onductivity)
sulation					
Element	Material	Nom. T	hickness	Nom. Insulation Diameter	Color Code

	Material	Nom. Thickness	Nom. Diameter
	PVC - Polyvinyl Chloride	0.043 in (1.1 mm)	0.423 in (10.7 mm)
Ī	Overall Cable Diameter (	Nominal): 0.423 in	(10.7 mm)

# **Electrical Characteristics**

# Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Velocity of Prop.	Max. Current
Conductor(s)	1.6 Ohm/1000ft	22.3 pF/ft (73.2 pF/m)	66%	24 Amps per conductor @ 30°C

## Voltage

UL Voltage Rating 300 V (CM, CL3)

# **Mechanical Characteristics**

## Temperature

<b>UL Temperature</b>	Operating
75°C	-20°C To +75°C

#### **Bend Radius**

Stationary Will. Ilistaliation w	***
4.2 in (110 mm) 4.2 in (110 mr	1)
Max. Pull Tension:	3
B # 0 11 W : 11	100 11 (10000
Bulk Cable Weight:	123 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor, Burial
Flammability / Reaction to Fire:	UL 1685 UL loading
NEC / UL Compliance:	Article 725, Article 800, CL3, CM
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6002UE

# **Product Notes**

Notes:	Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

#### History

Update and Revision:	Revision Number: 0.480 Revision Date: 02-03-2025

### **Part Numbers**

### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
1312A 010500	Black	Reel	500 ft	612825111672	С
1312A 0101000	Black	Reel	1,000 ft	612825111665	С
1312A 008500	Gray	Reel	500 ft	612825111658	С
1312A 0081000	Gray	Reel	1,000 ft	612825111641	С
1312A 1SL500	White 1SL	Reel	500 ft	612825111696	С
1312A 1SL1000	White 1SL	Reel	1,000 ft	612825111689	С

#### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.