
Project	Catalog #	Туре	
Prepared by	Notes	Date	



# **Metalux**

SK-12, SK-14, SK-22, SK-24

2x2, 2x4, 1x4, and 1x2 Surface Mount Kits Field Install Version

### **Typical Applications**

Plenum-less spaces. • Retrofits • Remodel projects

# Interactive Menu

- Product Specifications page 2
- Dimensional Details page 2
- Mounting Details page 3
- · Compatibility Matrix page 4
- Product Warranty

### **Product Certification**







### **Top Product Features**

- The Metalux universal field install surface mount kits allow for numerous recessed fixture families from Cooper Lighting Solution's to be installed in plenum-less spaces
- Ideal for retrofits, remodel projects, or where a recessed fixture is preferred but plenum space is not available
- Works with 2' x 2', 2' x 4', 1' x 4' and 1' x 2' Metalux, Fail-Safe and Corelite product series
- See Compatibility Matrix (page 4) and Ordering Information below for specific availability

### **Order Information**

Stock or MTO	Size	Catalog Number	Description	
Stock	2' x 4'	SK-24-WS	2' x 4' Surface Mount Kit, Shallow	
Stock	2' x 4'	SK-24-WT	2' x 4' Surface Mount Kit, Tall	
Stock	2' x 2' SK-22-WS 2' x 2' Surface Mount Kit, Shallow			
Stock	2' x 2'	SK-22-WT	2' x 2' Surface Mount Kit, Tall	
Stock	1' x 4'	SK-14-WT*	1' x 4' Surface Mount Kit, Tall	
Stock	1' x 2'	SK-12-WT	1' x 2' Surface Mount Kit, Tall	

NOTES: The weight of the installed luminaire (ONLY) not to exceed 40 lbs.

Flex cables sold separately.

Review Compatibility Matrix before placing order for recessed luminaire.

\*SkyRigd = 1' x 4' fixture with curved reflector ("-C-") does not fit the 1' x 4' kit without requirement for special bracket, please submit PDR request for order processing.



### **Product Specifications**

#### Construction

- Feature snap-together frame design constructed of dieformed 20 gauge cold rolled steel
- Both 2' x 2' and 2' x 4' kits are offered in two depths, a Shallow (4-15/16") and Tall (5-1/16") to accommodate an array of fixture types and options
- 1' x 4' and 1' x 2' are only offered in a Tall (5-1/16")
- Composite end caps provide simple snap on attachment to housing for convenience
- Additional safety #10 screws can be used if necessary at pre-tap locations
- Four access plate knockouts provide flexible installation and supply connection

- A set of four mounting points are provided for surface mounting, for pendant mount six mounting points are provided for either two or four point suspension
- Cooper Lighting Solutions SCA (1/2" O.D.) suspension sets (#SCA-48-B) are recommended for stem mounting

#### Finish

- Durable cold rolled steel housing is finished in high reflectance white using electrostatically applied polyester powder coat paint to ensure maximum rust inhibition
- End caps provide matching matte white finish.

### Compliance

Field install universal surface mount kits are UL recognized accessories

#### Mounting

 Both versions are designed to provide a means for surface or pendant mounting

#### Warranty

· One year warranty


### **Dimensional Details**

#### Incide

		SK-24-WS	SK-24-WT	SK-22-WS	SK-22-WT
Α	Width	24"	24"	24"	24"
В	Length	48-1/16"	48-1/16"	24-1/16"	24-1/16"
С	Height	4-15/16"	6-3/8"	4-15/16"	6-3/8"

#### Outside

		SK-24-WS	SK-24-WT	SK-22-WS	SK-22-WT
D	Width	24-1/4"	24-1/4"	24-1/4"	24-1/4"
E	Length	49-1/2"	49-1/2"	25-1/2"	25-1/2"
F	Height	5-1/16"	6-5/8"	5-1/16"	6-5/8"




### Inside

		SK-14-WT	SK-12-WT	
Α	Width	12"	12"	
В	Length	48-1/16"	24-1/16"	
С	Height	6-1/4"	6-1/4"	

### Outside

		SK-14-WT	SK-12-WT
А	Width	12-3/16"	12-3/16"
В	Length	49-7/16"	25-7/16"
С	Height	6-9/16"	6-9/16"



#### **Shipping Data**


Catalog No.	Wt.			
SK-22-WS	12 lbs.			
SK-24-WS	21 lbs.			
SK-22-WT	14 lbs.			
SK-24-WT	24 lbs.			
SK-14-WT	13 lbs.			
SK-12-WT	7 lbs.			







Metalux Surface Mount Kit


## **Mounting Details**






#### **Pendant Mounting**






### **Access Plate Location**



### Access Plate Location

ø 1/2"



Metalux **Surface Mount Kit** 

# Compatibility Matrix ✓ LED • Fluorescent

	Shallow Design		Tall Design			
	2' x 2' 2' x 4'		2' x 2'	2' x 4'		
	SK-22-WS	SK-24-WS	SK-22-WT	SK-24-WT	SK-14-WT	SK-12-WT
Metalux						
Accord	<b>✓</b>	<b>✓</b>			<b>✓</b>	
Cruze ST/SB	<b>✓</b>	<b>✓</b>			~	
Encounter	<b>✓</b>	<b>✓</b>			~	<b>V</b>
FP/FPX (1)	V	V			V	
GC			•	•	•	
GR	V	V			V •	
InDepth	<b>V</b>	<b>V</b>			V	
Ovation			<b>✓</b>		V	
Parabolics (4)			•	•		
Perceive PD	<b>✓</b>	<b>✓</b>			~	
RLN	V	<b>✓</b>			~	
SkyRidge (2)			<b>✓</b>	<b>✓</b>	~	<b>✓</b>
SP	V				~	
Fail-Safe (3)						
ENC/ENV/ENW	<b>✓</b>	V			~	<b>✓</b>
FCB	<b>✓</b>	~			~	
FCZ	<b>✓</b>	~			~	
FSP	<b>✓</b>	<b>✓</b>			~	
GRV	<b>✓</b>	<b>✓</b>			~	
GRW	<b>✓</b>	<b>✓</b>			~	
Corelite						
Class D3X	<b>✓</b>	<b>✓</b>			~	
Class R2X	<b>✓</b>	<b>✓</b>			~	
Class R3/Z3	<b>✓</b>	~			<b>✓</b>	
Class RX/ZX	<b>✓</b>	~			~	
InDepth	V	V			V	

Notes: (1) FP/FPX also compatible with other Surface Mount Kits. Consult specification sheets for more details.



<sup>(2)</sup> SkyRidge 1' x 4' fixture with curved reflector ("-C-") does not fit the 1' x 4' kit without requirement for special bracket, please submit PDR request for order processing.

<sup>(3)</sup> Fail-Safe fixtures with emergency do not fit either kit size.
(4) Covers 2P2G, 2EP3, 2HP2, 2HP3, OpticaHP; 2PGAX does not fit kits