



# HALO<sup>®</sup>

**LCR** Light Commercial Retrofit

Solutions for Mixed-Use and  
Light Commercial Spaces



**COOPER**  
Lighting Solutions



## Product Features



- Direct Mount 2", 4", 6" & 8" downlights
- Field Selectable 2700 / 3000 / 3500 / 4000 / 5000 K CCT; 90+ CRI
- Up to 8000lm ( 8" ), Up to 3000lm ( 6" ), Up to 1200lm ( 4" ), 800lm ( 2" )
- Wet location listed, suitable for shower applications
- Remote driver / junction box, 120-277V, 5% 0-10V dimming
- Held securely in 0.5" – 1.25" thick ceilings with retention springs
- Airtight and suitable for direct contact with insulation

The **LCR** is an LED downlight family with a remote driver / junction box positioned as HALO's light commercial solution for new construction and remodel applications.

## Value Proposition

- No housing required, reduces installation time and expense
- Wide distribution patterns are ideal for general area illumination
- High powered direct mounts with high CRI and efficiency
- Regressed lens provides high optical cutoff and improves visual comfort
- Residential, Office, Hospitality and Healthcare verticals



**LCR2**  
2-inch  
800 lumens



**LCR4**  
4-inch  
800 lumens | 1200 lumens



**LCR6**  
6-inch  
1500 lumens | 2100 lumens | 3000 lumens



**LCR8**  
8-inch  
3000 lumens | 5000 lumens | 8000 lumens

| Catalog Number  | Material Number | Description                                              | UPC          | Accessories    |                |                |                 |
|-----------------|-----------------|----------------------------------------------------------|--------------|----------------|----------------|----------------|-----------------|
|                 |                 |                                                          |              | Mounting Frame | Designer Trims | Oversized Trim | Extension Cable |
| LCR2089FSE010MW | 13261013        | 2.5" 800 lumen, LCR Direct Mount, Round, 120-277V, 0-10V | 080083889969 |                | •              |                | •               |
| LCR2089FS1EMW   | 13393464        | 2.5" 800 lumen, LCR Direct Mount, Round, 120V            | 080083130061 |                | •              |                | •               |
| LCR4089FSE010MW | 13261014        | 4" 800 lumen, LCR Direct Mount, Round, 120-277V, 0-10V   | 080083889983 | •              | •              | •              | •               |
| LCR4129FSE010MW | 13261015        | 4" 1200 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890002 | •              | •              | •              | •               |
| LCR6159FSE010MW | 13261016        | 6" 1500 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890026 | •              | •              | •              | •               |
| LCR6219FSE010MW | 13261017        | 6" 2100 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890040 | •              | •              | •              | •               |
| LCR6309FSE010MW | 13261018        | 6" 3000 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890064 | •              | •              | •              | •               |
| LCR8309FSE010MW | 13261019        | 8" 3000 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890088 | •              | •              | •              | •               |
| LCR8509FSE010MW | 13261140        | 8" 5000 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890101 | •              | •              | •              | •               |
| LCR8809FSE010MW | 13261141        | 8" 8000 lumen, LCR Direct Mount, Round, 120-277V, 0-10V  | 080083890125 | •              | •              | •              | •               |



mounting frame



designer trims



oversized trim ring



extension cable