







	Designation	Description
Open 	Blank= No Guard	For maximum light output
I5 / I8 Lens Frosted Acrylic Lens 	I5-FRM/LENS= Frosted Acrylic Lens and Frame (use with general distribution reflector, I5 only) I8-FRM/FL PK= Frosted Acrylic Lens and Frame (use with general distribution reflector, I8 only) I5-FRM/CL PK= Clear Acrylic Lens and Frame (use with general distribution reflector, I5 only) I8-FRM/CL PK= Clear Acrylic Lens and Frame (use with general distribution reflector, I8 only)	Lens in white door frame with "Herringbone" patterned end rail
I5/I8 Wireguard Heavy Duty Wireguard 	WG/I5-4FT-B= Four Foot (4') Heavy Duty Wireguard (for I5) WG/I8-4FT-B= Four Foot (4') Heavy Duty Wireguard (for I8)	Finished in White. Can be used alone or in combination with other shielding
I5/I8 Baffle TBW 	90800PPK BAFFLE 4FT I5 WITH HDW (WHITE)= Four Foot (4') Thin Blade White Baffle (for I5) BAFFLE 4FT I8 (WHITE) 11571919= Four Foot (4') Thin Blade White Blade Baffle (for I8)	Thin Blade White Baffle with twenty-three Degree (23°) longitudinal shielding
I5/I8 Louver Asymmetric Louver 	90801P PK= Asymmetric Directional Louver (use with general distribution reflector)	Can be oriented in either direction for flexibility

HBI Lens and Wireguard	Designation
Prismatic and Clear Acrylic Lens 	HBI-FRM/LENS PK = Prismatic Acrylic Lens and Door Frame for HBI
	HBI-FRM/CL PK = Clear Acrylic Lens and Door Frame for HBI
Wireguard 	HBI-FRM/WG PK = Frame and Wireguard for HBI
	HBI-FRM/LENS/WG PK = Frame and Prismatic Acrylic Lens with Wireguard for HBI
	HBI-FRM/CL/WG PK = Frame and Clear Lens with Wireguard for HBI
Drop Wireguard 	HBI-FRM/DROP/WG PK = Frame and Drop Wireguard for HBI
	HBI-FRM/CL/DROP/WG PK = Drop Wireguard, Clear Acrylic Lens and Door Frame for HBI
Heavy Duty Stock Wireguard 	SWG/HBI-4FT-B = Heavy Duty Wireguard for Field Installation
HBL Wireguard	Designation
Wireguard 	WG-HBL6-4FT-B = Field Installable, Wireguard for HBL 4 and 6 Lamp
	WG-HBL8-4FT-B = Field Installable, Wireguard for HBL 8 and 10 Lamp
HBE Door Frame	Designation
HBE Door Frame 	HBE-___-FRM/LENS WDF PK = Prismatic Acrylic Lens and Extruded Aluminum Door Frame ¹
	HBE-___-FRM/CL WDF PK = Clear Acrylic Lens and Extruded Aluminum Door Frame ¹
	HBE-___-FRM/LENS/WG WDF PK = Four (4) and Six (6) Lamp Frame and Prismatic Lens with Wireguard ¹
	HBE-___-FRM/LENS/WG PK = Eight (8) and Ten (10) Lamp Frame and Prismatic Lens with Wireguard ¹
	HBE-___-FRM/CL/WG PK = Four (4) and Six (6) Lamp Frame and Clear Acrylic Lens with Wireguard ¹
	HBE-___-FRM/CL/WG WDF PK = Eight (8) and Ten (10) Lamp Frame and Clear Acrylic Lens with Wireguard ¹

NOTES: 1. Specify "4/6LT" or "8/10LT" when ordering HBE Door Frame accessories.

