E26 5" Trim Series

DESCRIPTION


Coilex® tapered baffle trim with self-flange in the 5" trim family for use in recessed downlighting. Compatible for use in Halo and other housings.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

SPECIFICATION FEATURES

- Contoured tapered sides of Coilex baffle for BR30 and PAR30 lamps
- · Coil spring retention
- Self-flanged trim ring sized to hide gaps caused by construction tolerances.

IC



Housings		Max Lamp Compatibility			
H5ICAT	H5RICAT	ENW DADOG COW DADOU COW DDO			
E5ICAT	E5RICAT	50W PAR30S, 60W PAR30L, 60W BR30			
H25ICAT		39W PAR30S, 60W PAR30L, 50W BR30			
H5T	H5RT	75\A/ DA DOOC 75\A/ DA DOOL 65\A/ DDOO			
E5TAT E5RTAT		75W PAR30S, 75W PAR30L, 65W BR30			
Compatible with Halogen Incandescent LED* or CEL* lamps					


Compatible with Halogen, Incandescent, LED* or CFL* lamps



5109WBWhite Coilex® Baffle,
White Trim



5109BB Black Coilex® Baffle, White Trim



5109BKBB Black Coilex® Baffle, Black Trim

5109

5-Inch Coilex® Tapered Baffle, Self-flange

Dimensions:

A: 4-3/4" [121mm] H: 2-3/8" [60mm] OD: 6-5/8" [168mm]

ORDERING INFORMATION

SAMPLE NUMBER: 5109WB

Trim		Finish		
	5109 = 5" Coilex® Tapered Baffle, Self-flange	WB=Matte White baffle, Matte White trim BB=Black baffle, White trim BKBB=Black baffle, Black trim		

HALO HOUSING COMPATIBILITY

Trim#	Style	H5ICAT	H5RICAT	E5ICAT	E5RICAT	H25ICAT	H5ICATNB	E5ICATNB	H25ICATNB
		•	•	•	•	•	_	_	_
5109	Baffle	H5T	H5RT	E5TAT	E5RTAT	H5TNB	E5TATNB		
		•	•	•	•	_	_		

For use in other's housings, refer to U.L. Classification list at www.cooperlighting.com.



For use in Halo listed housings.



Select trims are classified for use in others housings. See www.cooperlighting.com.

^{*}UL1993 listed LED & CFL equivalent lamps permitted. Consult lamp manufacturer for conditions of use. Cooper Lighting Solutions does not warranty the lamp.