

E26 5" Trim Series


DESCRIPTION

Open wet location, full reflector trim with self-flange in the 5" trim family for use in recessed downlighting. Compatible for use in Halo and other housings. For use with outdoor rated lamps only.

Catalog #		Type
Project		
Comments		Date
Prepared by		

SPECIFICATION FEATURES

- Open wet location metal showerlight
- Outdoor rated lamps ONLY
- Torsion spring retention
- Socket supporting
- Self-flanged trim ring sized to hide gaps caused by construction tolerances
- For use in standard and shallow housings



Dimensions:

A: 4-13/16" [121mm]
H: 6-5/16" [160mm]
OD: 6-5/8" [168mm]

Housings	Max Lamp Compatibility
H5ICAT H5RICAT	50W PAR30S, 60W PAR30L
E5ICAT E5RICAT	
H5ICATNB	50W PAR30S, 60W PAR30L
E5ICATNB	
H5T H5RT	75W PAR30S, 75W PAR30L
E5TAT E5RTAT	
H5TNB	75W PAR30S, 75W PAR30L
E5TATNB	

Compatible with Halogen, Incandescent, LED* or CFL* lamps.




Lamp Gasket
(included)



5146WH
White Reflector and Trim



5146SN
Satin Nickel Reflector and Trim



5146TBZ
Tuscan Bronze Reflector and Trim

5146

5-Inch Open Wet Location,
Full Reflector,
Self-flange



ORDERING INFORMATION

SAMPLE NUMBER: 5130WH

Trim	Finish
5146= 5" Open wet location, Full reflector, self-flange	WH=Matte White trim SN=Satin Nickel trim TBZ=Tuscan Bronze trim

HOUSING COMPATIBILITY

Trim #	Style	H5ICAT	H5RICAT	E5ICAT	E5RICAT	H25ICAT	H5ICATNB	E5ICATNB	H25ICATNB
5146	Open Showerlight	•	•	•	•	—	•	•	—
		H5T	H5RT	E5TAT	E5RTAT	H5TNB	E5TATNB		
		•	•	•	•	•	•		

For use in other's housings, refer to U.L. Classification list at www.cooperlighting.com



Select trims are classified for use in others housings.
See www.cooperlighting.com

*UL1993 listed LED & CFL equivalent lamps permitted. Consult lamp manufacturer for conditions of use. Cooper Lighting Solutions does not warranty the lamp.