


Project		Catalog #		Type	
Prepared by		Notes		Date	



HALO

LCR6

6-Inch Round All-Purpose LED Retrofit Module

Typical Applications

Residential • Multi-family • Mixed-Use

Interactive Menu

- Order Information [page 2](#)
- Product Specifications [page 2](#)
- Photometric Data [page 3](#)
- Energy & Performance Data [page 3](#)
- Product Warranty
- Dimming Guide

Product Certification



Refer to ENERGY STAR® Certified Products List.
Can be used to comply with California Title 24 High Efficacy requirements.
Certified to California Appliance Efficiency Database under JAB.

Product Features




Top Product Features


- Select from 5 CCTs via switch; 2700K, 3000K, 3500K, 4000K, 5000K CCT; 90 CRI
- Up to 3000 Lumens; IC rated
- Direct mount - does not require recessed housing or junction box
- Dimmable down to 5%, 0-10V
- Wet location listed for showers and protected ceilings

Dimensional and Mounting Details

1500 lumen / 2100 lumen



6" round cutout



additional product diagrams

Order Information

SAMPLE ORDER NUMBER: **LCR6159FSE010MW**

Models	Lumens	CRI/CCT	Driver	Finish
LCR6 = 6" all-purpose round LED module	15 = 1500 lumens (nominal) 21 = 2100 lumens (nominal) 30 = 3000 lumens (nominal)	9FS = 90 CRI minimum, field selectable CCT, choose 2700K, 3000K, 3500K, 4000K or 5000K CCT	E010 = UNV 120 - 277V, 50/60Hz, 0-10V analog 100% to 5% dimming	MW = Matte white
Notes	Notes	Notes	Notes	Notes

Accessories

Accessories	
Overized Trim Ring HLB6ROTMMW = Oversize trim ring for 6" housings Designer Trims LCR6TRMAH = 6" Haze, white flange LCR6TRMSC = 6" Specular, white flange LCR6TRMTBZ = 6" Tuscan bronze LCR6TRMWH = 6" Paintable white	Mounting Frame HLB6RSMF = 6" round and square mounting frame Extension Cable selectable Driver/Jbox HLB06FSEC – 6 ft. extension cable HLB12FSEC – 12 ft. extension cable HLB20FSEC – 20 ft. extension cable

Product Specifications

Module

- Module construction includes LED Array, reflector, lens, housing and heat sink where applicable
- Integral aluminum heat sink provides passive thermal cooling achieving L70 at 50,000 hours in IC and non-IC applications

LED Array

- Mid power LED array provides a uniform source with high efficiency and no pixilation.
- 90 CRI minimum, R9 greater than 50
- Color accuracy within 3 SDCM at the CCT endpoints and 4 SDCM in between endpoints, provide color accuracy and uniformity.
- Correlated Color Temperature (CCT) has a selectable range from 2700K to 5000K (factory default 3000K)
- Use the switch to choose between 2700K, 3000K, 3500K, 4000K, and 5000K CCT

Optical Assembly

- Regressed flat lens provides uniformity, UGR ≤ 10
- Exceeds ENERGY STAR® color angular uniformity requirements

Remote Driver/Junction Box

- Metal driver/junction box with captive hinged junction box cover. Listed for (6) #12 AWG 90°C splice conductors, 2-in, 2-out plus (2) ground
- (4) 1/2" conduit pry-outs
- (2) Slide-N-Side™ non-metallic (NM) wire traps all accepts 14-2, 14-3, 12-2, 12-3 U.S and 14-2, 14-3, 12-2 Canadian NM cable

- (3) 4-port push wire nuts with clear caps for quick and reliable mains voltage connections
- Integral keyhole mounting slots facilitate direct mounting to building structure or new construction mounting frame

Driver

- Integral 120-277V, 50/60Hz constant current driver provides noise free operation
- Continuous, flicker-free dimmer from 100% to 5%
- Plenum rated inline electrical quick connect provides low voltage connection to fixture fitting

Installation

- Can be installed in 3/8" to 1-1/4" thick ceilings
- Cutout can utilize standard round hole saw sizes, cutout template provided
- Mousetrap springs hold fixture fitting securely in the ceiling eliminating light leaks
- Can be removed from below the ceiling for service or replacement

Mounting / Retention

- The LCR6 requires no housing or third party junction box
- The remote enclosure may be used in direct contact with insulation.
- Installer must cut template out of drywall and install into aperture with the clips compressed.
- When released, the mousetrap springs will rest on to the back side of the drywall
- Not for installation in recessed cans


Compliance

- UL certified US and Canada
- Wet location listed and IP64 ingress protection rated, covered ceiling only
- Airtight per ASTM-E283-04
- Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements
- EMI/RFI emissions per FCC 47CFR Part 15 consumer limits, CAN ICES-005(B)/NMB-005 (B)
- Contains no mercury or lead and RoHS compliant
- Photometric testing in accordance with IES LM-79-08
- Lumen maintenance projections in accordance with IES LM-80-08 and TM-21-11
- Can be used for State of California Title 24 high efficacy LED compliance under JA8, reference Modernized Appliance Efficiency Database System (MAEDBS) for 2019 JA8 High Efficacy Lighting
- ENERGY STAR® certified, reference "Certified Light Fixtures" database

Warranty

- Five year limited warranty, consult website for details. www.cooperlighting.com

Photometric Data

[View IES files](#)
**LCR6159FSE010MW**

Spacing criterion: (0-180) 1.14
(90-270) 1.14
(Diagonal) 1.21

Beam Angle: 86°
Lumens: 1609
Input Watts: 15.85 W
Efficacy: 101.5 LPW
Test Report:
LCR6159FSE010MW.IES


Zonal Lumen	Lumens	% Lumens
0-30	633	39.3
0-40	996	61.9
0-60	1490	92.6
0-90	1607	99.9

TM-30-15	Rf = 94
	Rg = 99
CRI/CIE	Ra = 95
	R9 = 67

CCT - Range of 2700K- 5000K



86°

**LCR6219FSE010MW**


Spacing criterion: (0-180) 1.15
(90-270) 1.15
(Diagonal) 1.21

Beam Angle: 86°
Lumens: 2348
Input Watts: 24.26 W
Efficacy: 96.8 LPW
Test Report:
LCR6219FSE010MW.IES


Zonal Lumen	Lumens	% Lumens
0-30	921	39.2
0-40	1449	61.7
0-60	2172	92.5
0-90	2344	99.8

TM-30-15	Rf = 93
	Rg = 99
CRI/CIE	Ra = 95
	R9 = 65

CCT - Range of 2700K- 5000K



86°

**LCR6309FSE010MW**

Spacing criterion: (0-180) 1.14
(90-270) 1.14
(Diagonal) 1.21

Beam Angle: 86°
Lumens: 3055
Input Watts: 29.41 W
Efficacy: 103.9 LPW
Test Report:
LCR6309FSE010MW.IES

Zonal Lumen	Lumens	% Lumens
0-30	1200	39.3
0-40	1884	61.7
0-60	2823	92.4
0-90	3049	99.8

TM-30-15	Rf = 94
	Rg = 100
CRI/CIE	Ra = 96
	R9 = 72

CCT - Range of 2700K- 5000K



86°

Energy and Performance Data

LCR6159FSE010MW		
	120V	277V
Lumens	1613 @ 4000K	
Input Voltage	120-277V	
Input Frequency	50/60Hz	
Input Power	16.33W	16.45W
Input Current	0.137A	0.067A
Power Factor	>0.90	
THD	<20%	
EMI/RFI	FCCTitle 47 CFR, Part 15, Class B CAN ICES-005(B)	
Sound Rating	Class A	
Minimum Starting Temp	-30°C (-22°F)	

LCR6219FSE010MW		
	120V	277V
Lumens	2333 @ 3500K	
Input Voltage	120-277V	
Input Frequency	50/60Hz	
Input Power	25.08W	24.36W
Input Current	0.211A	0.097A
Power Factor	>0.90	
THD	<20%	
EMI/RFI	FCCTitle 47 CFR, Part 15, Class B CAN ICES-005(B)	
Sound Rating	Class A	
Minimum Starting Temp	-30°C (-22°F)	


LCR6309FSE010MW		
	120V	277V
Lumens	2999 @ 4000K	
Input Voltage	120-277V	
Input Frequency	50/60Hz	
Input Power	30.66W	30.28W
Input Current	0.257A	0.115A
Power Factor	>0.90	
THD	<20%	
EMI/RFI	FCCTitle 47 CFR, Part 15, Class B CAN ICES-005(B)	
Sound Rating	Class A	
Minimum Starting Temp	-30°C (-22°F)	

Tested in accordance with IES LM63. Field results may vary.


Note: Refer to IES files for more product data.

Dimensional Details


1500 lumen / 2100 lumen



6" round cutout



3000 lumen



6" round cutout

