

DESCRIPTION

The HALO entry light provides dependable security lighting with nighttime ON and daytime OFF functionality. Suitable for mounting heights up to 10ft, these fixtures are ideal for residential applications such as entrances, patios and walkways. Produces light output equivalent to 75W incandescent, available in white or bronze finish.

| Catalog # | | Type |
|-------------|--|------|
| Project | | |
| Comments | | Date |
| Prepared by | | |

SPECIFICATION FEATURES

Construction

- Corrosion resistant polycarbonate housing
- UV stable frosted polycarbonate lens
- Available in bronze or white finish
- Suitable for recessed junction boxes

Electrical

- Maintenance-free LEDs with 25,000 hours of life
- Fixture operating temperature range from -30°C to 40°C
- Integral photo control included
- Electrical operating voltage 120VAC 60Hz
- cULus listed for wet locations
- External supply wiring 75°C minimum

Optics

- Diffused lens
- 5000K CCT

Warranty

5 year limited warranty




**FE0650
LED ENTRY
LIGHT**


DIMENSIONS

FE0650LPC

Front View



Side View



ORDERING INFORMATION

| Model | Finish |
|------------|--------|
| FE0650LPC | Bronze |
| FE0650LPCW | White |


CERTIFICATION DATA

cULus Wet Location Listed

TECHNICAL DATA

-30°C to 40°C Temperature Rating
External Supply Wiring 75° Minimum
Wall and Pole Mount

PHOTOMETRICS



| | 0.25 Fc Coverage Area | | | | | |
|-----------------|-----------------------|----|----|----|-----|----|
| Mounting Height | 8 | | 10 | | 15 | |
| Catalog Number | X | Y | X | Y | X | Y |
| FE0650 Series | 13 | 24 | 13 | 24 | 8.5 | 17 |

X = Forward Throw
Y = Wall Spread
Z = Mounting Heights

Technical Information

| | | Voltage (V) | Power (W) | Delivered Lumens | Efficacy (Lum/Watt) | LED Color Temperature (K) | CRI |
|----------------------|--------|-------------|-----------|------------------|---------------------|---------------------------|-----|
| FE0650 Series | Bronze | 120 | 9 | 811 | 91 | 5000 | 83 |
| | White | 120 | 9 | 927 | 104 | 5000 | 83 |