



BIBS2506MT

by Burndy
Catalog ID: BIBS2506MT

Prop 65 Notice

MOUNTING VERSIONMULTI-PORTSsingle-Sided Entry.

Product Details

General

| | |
|---------------------------------------|---------------|
| Hex Key | 5/16 |
| Insulation | Y |
| Insulation Type | Plastisol |
| Material | Aluminum |
| Number Of Ports | 6 |
| Physical Attribute - Number of Screws | 8 |
| Physical Attribute - Screw Type | Allen |
| Plated | N |
| Plating Type | Unplated |
| Temperature Rating | 194 |
| Trade Name | UNITAP™ |
| UPC | 781810252925 |
| UPC 12 Digit | 7818102529255 |

Dimensions

| | |
|---------------------------------|---------|
| Dimension - Height inch | 2.63 in |
| Dimension - L Length Overall mm | 194 mm |
| Dimension - Length Overall inch | 7.65 in |
| Dimension - Width inch | 1.95 in |
| Dimension - Width mm | 50 mm |

Electrical Ratings

| | |
|--------------------------|-----|
| Rating - Minimum Voltage | 600 |
|--------------------------|-----|

Conductor Related

| | |
|-----------------------------------|--|
| Conductor - AL Str Size Range | 10 - 250 Str |
| Conductor - Copper Str Size Range | 10 - 250 Str |
| Conductor Type | <ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size |

Certifications and Compliance

| | |
|------------------------------|-----|
| Certification - CSA Approved | Yes |
|------------------------------|-----|

| | |
|---|-------|
| Certification - ETL | No |
| Certification - UL Listed Direct Burial | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL467 |
| Standards - Industry Standards Met | UL467 |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 5 |
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)