



CL/CLM/SOLB/TWCL/DS SERIES

# KILLARK

## PULLING ELBOW & DUCT SEAL • STANDARD AND HOSTILE LOCATIONS



Duct seal

UL LISTED - File E E22699

SP Certified - File LR11852

See files for details or call Killark.

### FEATURES-SPECIFICATIONS

#### Applications

- 90° pulling elbows are used to accommodate pulling conductors through a sharp bend in the conduit system

#### Features

- Designed for easier wire pulling
- Includes Cover and Gasket

#### Material/Finish

**Copper-free Aluminum**  
(less than 4/10 of 1%)

- Electrostatically applied powder coating

#### PULLING ELBOWS FOR THREADED CONDUIT

CATALOG NUMBER	HUB SIZE	TYPE
CL-1	1/2"	CL
CL-2	3/4"	
CL-3	1"	
CLM-1	1/2"	CLM
CLM-2	3/4"	
CLM-3	1"	

© Raintight/concrete tight

#### PULLING ELBOWS FOR THINWALL CONDUIT

CATALOG NUMBER	HUB SIZE
TWCL-1	1/2"
TWCL-2	3/4"

© Set screw in each hub

Duct Seal is a soft, non-hardening weather-proof compound, easily applied in all working temperatures. It is non-staining, can be painted, is an excellent moisture barrier for weather-sealing service entries, electrical cables, conduit ducts, etc.

DUCT SEAL	
CATALOG NUMBER	SIZE
DS-1	1-lb.
DS-5	5-lb.

DIMENSIONS					
SIZE	A	B	C	D	E
1/2"	1-1/4" (32)	2-9/16" (65)	1-3/8" (35)	1-1/4" (32)	1-7/16" (37)
3/4"	1-3/8" (35)	2-3/4" (70)	1-9/16" (40)	1-3/8" (35)	1-17/32" (39)
1"	1-3/4" (44)	3-1/8" (79)	1-3/4" (44)	1-3/4" (44)	1-23/32" (44)

