



## KVS34

by Burndy  
Catalog ID: KVS34

Prop 65 Notice

Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURIUM bolts in place during installation. Installed with ordinary wrench. Recommended tightening torque: 375 in-lb.

Features: Compact, Two-Piece, High Strength, High Copper Alloy BURNDY OKLIP Recommended For Heavy Duty Connections, Neoprene Rings Hold DURIUM Bolts In Place During Installation, Installed With Ordinary Wrench, Conductor Type: Run And Tap: Copperweld, Commercial Stranded Copper, Solid Copperweld, Installation Torque: 375 IN-LB, Conductor Spacer: No

## Product Details

### General

|                                       |                        |
|---------------------------------------|------------------------|
| Application                           | For Copper, Copperweld |
| Installation Torque Recommended in-lb | 375 LBS/in             |
| Material                              | Copper                 |
| Plated                                | N                      |
| Plating Type                          | Unplated               |
| Sub Brand                             | OKLIP                  |
| Trade Name                            | OKLIP™                 |
| Type                                  | KVS, Compact           |
| UPC                                   | 781810063200           |
| UPC 12 Digit                          | 7818100632000          |

### Dimensions

|                            |         |
|----------------------------|---------|
| Dimension - Height inch    | 2.65 in |
| Dimension - Stud Size inch | 1/2 in  |
| Dimension - Width inch     | 2.20 in |

### Conductor Related

|                                  |  |
|----------------------------------|--|
| Conductor - Copper Str Run Range | 400 kcmil - 500 kcmil  |
| Conductor - Copper Str Tap Range | 10 str. - 500 kcmil  |
| Conductor Type                   | <ul style="list-style-type: none"> <li>• CU C Str-Run</li> <li>• CU C Str-Tap</li> <li>• CU Weld C Solid-Run</li> <li>• CU Weld C Solid-Tap</li> </ul> |

### Certifications and Compliance

|                               |        |
|-------------------------------|--------|
| Certification - CSA Approved  | No     |
| Certification - ETL           | No     |
| Certification - UL Recognized | No     |
| Certification - cULus         | No     |
| Industry Standard(s)          | UL486C |

|                                    |        |
|------------------------------------|--------|
| Standards - Industry Standards Met | UL486C |
| Standards - RoHS Compliance Status | CM     |
| UL Listed                          | Yes    |

## Logistics

|                       |   |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

### For further technical assistance, please contact us

#### **BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

#### **Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)