

CAT NO. BLACK	CAT NO. GRAY	NPT THREAD SIZE (METRIC DESIGNA-TOR)	CONDUIT TRADE SIZE (METRIC DESIGNA-TOR)	- A - INCH (mm)	- B - INCH (mm)	- C - INCH (mm)	- D - INCH (mm)	- E - INCH (mm)	- F - INCH (mm)	- G - INCH (mm) A/C*	- H - INCH (mm) A/F*	- I - INCH (mm)
PS0389NBK	PS0389NGY	1/2 (16)	3/8 (12)	1.30 (33.0)	3.27 (83.1)	0.57 (14.5)	0.55 (14.0)	1.43 (36.3)	2.00 (50.8)	1.41 (35.8)	1.30 (33.0)	0.875 (22.2)
PS0509NBK	PS0509NGY	1/2 (16)	1/2 (16)	1.30 (33.0)	3.27 (83.1)	0.57 (14.5)	0.55 (14.0)	1.43 (36.3)	2.00 (50.8)	1.41 (35.8)	1.30 (33.0)	0.875 (22.2)
PS0759NBK	PS0759NGY	3/4 (21)	3/4 (21)	1.53 (38.9)	3.66 (93.0)	0.58 (14.7)	0.74 (18.8)	1.59 (40.4)	2.23 (56.6)	1.65 (41.9)	1.53 (38.9)	1.109 (28.2)
PS1009NBK	PS1009NGY	1 (27)	1 (27)	1.80 (45.7)	4.00 (101.6)	0.72 (18.3)	0.96 (24.4)	1.84 (46.7)	2.30 (58.4)	1.94 (49.3)	1.80 (45.7)	1.375 (34.9)

*A/C = ACROSS CORNERS, A/F = ACROSS FLATS

NOTES:
1. MATERIAL: 6/6 NYLON
2. TEMPERATURE RANGE: -30°F (-34°C) TO 225°F (107°C).
3. COLORS: SEE TABLE
4. RoHS COMPLIANCE: CONNECTORS MEET EU DIRECTIVE, RESTRICTION OF THE USE OF CERTAIN HAZARDOUS SUBSTANCE IN ELECTRICAL OR ELECTRONIC EQUIPMENT.
5. AGENCY APPROVALS - UL LISTED AND CSA CERTIFIED.
6. PRIMARY DIMENSIONS ARE INCHES. UNITS IN SI ARE PROVIDED AS REFERENCE ONLY.
7. TOLERANCES: XX±.02, XXX±.005, ANGLES ±1°. GENERAL TOLERANCES DO NOT APPLY.



SUGGESTED CLEARANCE HOLE FOR NON THREADED MOUNTING

CAGE CODE 74545

LIST OF PARTS

DESCRIPTION	MATERIAL	FINISH
CONNECTOR	NYLON	BLACK/GRAY
O-RING	ELASTOMER	BLACK
LOCK NUT	NYLON	NATURAL/BLACK
FERRULE	NYLON	BLACK
COMPRESSION NUT	NYLON	BLACK/GRAY

REV	DESCRIPTION	APP	DATE
4	LIST OF PARTS- LOCKNUT NYLON, NATURAL/BLACK WAS NATURAL PER DCN 23596. RM	EJM	2/21/18
3	LIST OF PARTS- LOCKNUT NYLON, NATURAL WAS STEEL, ZINC PLATE PER DCN 23274. RM	EJM	2/1/18
2	CAT.NO.S IN TABLE UPDATED TO REFLECT NO. CALLED OUT ON DCN 22362, UPDATED NOTE 4 PER DCN 23274. MYA	DJP	8/15/17
1	NEW RELEASE PER DCN 22362 MYA	FFS	9/21/16

THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE. DIMENSIONS ARE IN INCHES [mm].

TITLE: LIQUID-TIGHT NON- METALLIC SWIVELLOK FITTING

WIRING DEVICE-KELLEMS
HUBBELL INCORPORATED
SHELTON, CT

TOLERANCES UNLESS OTHERWISE SPECIFIED
.XX = ± .01
.XXX= ± .005
ANGLE TOL. ±2°

DR. BY MALLEN | SCALE NONE
CHK. BY FFS | DATE 9/21/16

DIMENSION SHEET FOR CAT. NO.

B | M-13462 | 4