

Ground Fault Products



Meets UL Standard 943
Class A GFCI

Features and Benefits

Heavy Duty Commercial Tamper and Weather Resistant GFCI Receptacles

- Patented shutter design for tamper-resistant protection
- Meets NEC® requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired



Tamper-Resistant Weather Resistant

| Rating | Color | Standard | Assembled in USA | Isolated Ground | SNAPConnect® | Right Angle Pigtailed Terminal | | |
|--------------|--------------|-------------|------------------|-----------------|-----------------|--|-------------------------|----------------------------------|
| | Black | GFTWRST15BK | GFTWRST15BKU | GFTWRST15BKIG | GFTWRST15SNAPBK | Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material. | | |
| | Brown | GFTWRST15 | GFTWRST15U | GFTWRST15IG | GFTWRST15SNAP | | | |
| | Gray | GFTWRST15GY | GFTWRST15GYU | GFTWRST15GYIG | GFTWRST15SNAPGY | | | |
| | Ivory | GFTWRST15I | GFTWRST15IU | GFTWRST15IIG | GFTWRST15SNAPI | | | |
| | Light Almond | GFTWRST15LA | GFTWRST15LAU | GFTWRST15LAIG | GFTWRST15SNAPLA | | | |
| | Orange | — | — | GFTWRST15ORIG | — | | | |
| | Red | GFTWRST15R | GFTWRST15RU | GFTWRST15RIG | GFTWRST15SNAPR | | Solid SNAP1RA | |
| | White | GFTWRST15W | GFTWRST15WU | GFTWRST15WIG | GFTWRST15SNAPW | | Stranded SNAP2RA | |
| | | Black | GFTWRST20BK | GFTWRST20BKU | GFTWRST20BKIG | | GFTWRST20SNAPBK | Same as above. Assembled in USA. |
| | | Brown | GFTWRST20 | GFTWRST20U | GFTWRST20IG | | GFTWRST20SNAP | |
| Gray | | GFTWRST20GY | GFTWRST20GYU | GFTWRST20GYIG | GFTWRST20SNAPGY | | | |
| Ivory | | GFTWRST20I | GFTWRST20IU | GFTWRST20IIG | GFTWRST20SNAPI | | | |
| Light Almond | | GFTWRST20LA | GFTWRST20LAU | GFTWRST20LAIG | GFTWRST20SNAPLA | | | |
| Orange | | — | — | GFTWRST20ORIG | — | | | |
| Red | | GFTWRST20R | GFTWRST20RU | GFTWRST20RIG | GFTWRST20SNAPR | Solid SNAP1RNA | | |
| White | | GFTWRST20W | GFTWRST20WU | GFTWRST20WIG | GFTWRST20SNAPW | Stranded SNAP2RNA | | |



Hospital Grade ● Tamper-Resistant Weather Resistant

| Rating | Color | Standard | Assembled in USA | Isolated Ground | SNAPConnect® | Right Angle Pigtailed Terminal | | |
|--------------|--------------|-------------|------------------|-----------------|-----------------|--|-------------------------|----------------------------------|
| | Black | GFTWRST82BK | GFTWRST82BKU | GFTWRST82BKIG | GFTWRST82SNAPBK | Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material. | | |
| | Brown | GFTWRST82 | GFTWRST82U | GFTWRST82IG | GFTWRST82SNAP | | | |
| | Gray | GFTWRST82GY | GFTWRST82GYU | GFTWRST82GYIG | GFTWRST82SNAPGY | | | |
| | Ivory | GFTWRST82I | GFTWRST82IU | GFTWRST82IIG | GFTWRST82SNAPI | | | |
| | Light Almond | GFTWRST82LA | GFTWRST82LAU | GFTWRST82LAIG | GFTWRST82SNAPLA | | | |
| | Orange | — | — | GFTWRST82ORIG | — | | | |
| | Red | GFTWRST82R | GFTWRST82RU | GFTWRST82RIG | GFTWRST82SNAPR | | Solid SNAP1RA | |
| | White | GFTWRST82W | GFTWRST82WU | GFTWRST82WIG | GFTWRST82SNAPW | | Stranded SNAP2RA | |
| | | Black | GFTWRST83BK | GFTWRST83BKU | GFTWRST83BKIG | | GFTWRST83SNAPBK | Same as above. Assembled in USA. |
| | | Brown | GFTWRST83 | GFTWRST83U | GFTWRST83IG | | GFTWRST83SNAP | |
| Gray | | GFTWRST83GY | GFTWRST83GYU | GFTWRST83GYIG | GFTWRST83SNAPGY | | | |
| Ivory | | GFTWRST83I | GFTWRST83IU | GFTWRST83IIG | GFTWRST83SNAPI | | | |
| Light Almond | | GFTWRST83LA | GFTWRST83LAU | GFTWRST83LAIG | GFTWRST83SNAPLA | | | |
| Orange | | — | — | GFTWRST83ORIG | — | | | |
| Red | | GFTWRST83R | GFTWRST83RU | GFTWRST83RIG | GFTWRST83SNAPR | Solid SNAP1RNA | | |
| White | | GFTWRST83W | GFTWRST83WU | GFTWRST83WIG | GFTWRST83SNAPW | Stranded SNAP2RNA | | |

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.