


**EMT COMPRESSION COUPLINGS**

Compression Couplings, Steel

**B06**

Catalog #: 2926

**APPLICATIONS**

For use in dry locations to couple two ends of EMT conduit  
 RACO Compression couplings are suitable for applications above 600V

**PRODUCT FEATURES**

RACO Steel compression couplings provide concrete-tight connections  
 All steel construction ensures mechanical protection for the raceway  
 All components are zinc electroplated for corrosion protection  
 UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation.

**CULUS**

Standard 514B, UL Listed E195970, C22.2 No. 18

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf)

**GENERAL PRODUCT INFORMATION**

Trade Size: 1-1/2 in.

**DRAWING DIMENSIONS**

Dimension A: 2.78 in.  
 Dimension B: 2.27 in.

**PACKAGING**

Package Type: Carton  
 Ship Carton Qty.: 20  
 Product UPC-A Labeled: No  
 Weight (Lbs. Per/C): 53.20  
 Ship Carton Length (in.): 11.86  
 Ship Carton Width (in.): 9.50  
 Ship Carton Height (in.): 3.77  
 Ctn Weight (Lbs.): 10.65  
 UPC Number: 050169029268  
 I2of5: 50050169029263