FLEXIBLE METAL SQUEEZE CONNECTORS - DIE CAST ZINC

Straight Squeeze Connectors, Uninsulated Die Cast Zinc
N/A **B64**



Catalog #: 2195RAC

APPLICATIONS

For use in dry locations to bond armored cable to a box or enclosure
N/A

PRODUCT FEATURES

Rugged metallic construction insures mechanical protection for the raceway

UL LISTED

Standard 514B, File E195969

CSA

C22.2 No. 18

GENERAL PRODUCT INFORMATION

Trade Size:	1-1/4 in.

DRAWING DIMENSIONS

Dimension A:	43/64 in.
Dimension B:	1-31/32 in.
Dimension C:	1-47/64 in.
Dimension D:	NO. 12 x 1.25
Dimension E:	1-1/4 in. - 11-1/2 NPSM

PACKAGING

Package Type:	Carton
Std. Pkg.:	10
Ship Carton Qty.:	100
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	25.00
Ship Carton Length (in.):	19.00
Ship Carton Width (in.):	10.95
Ship Carton Height (in.):	8.00
Ctn Weight (Lbs.):	29.60
UPC Number:	050169021958
I2of5:	50050169021953