



GX3434

by Burndy
Catalog ID: GX3434

Prop 65 Notice

Cast Cu Alloy Ground Connector, 300 - 500 Kcmil(A), 300 - 500 Kcmil(AA), 3/4" Rod Dia., Bronze H/W

Product Details

General

Installation Torque Recommended in-lb	480 LBS/in
Material	Copper Alloy
Material Type - Screw	DURIUM™ Silicon Bronze
Plated	N
Plating Type	Unplated
U Bolt Type	256
UPC	781810260739
UPC 12 Digit	7818102607399

Dimensions

Dimension - Height fraction	4-1/4 in
Dimension - Height inch	4.25 in
Dimension - L Length Overall mm	67 mm
Dimension - Length Overall inch	2.62 in
Dimension - Width fraction	2-5/8 in
Dimension - Width inch	2.63 in
Dimension - Width mm	67 mm

Conductor Related

Conductor - Copper Str Size A	300;350;400;450;500
Conductor - Copper Str Size A Range	300-500
Conductor - Copper Str Size B	300;350;400;450;500
Conductor - Copper Str Size B Range	300-500
Conductor - Copper Tube Std Size	0.75
Conductor Type	• CU C Str-Size A • CU C Solid-Size A • CU C Str-Size B • CU C Solid-Size B

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes

Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	4
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)