WRAPS

PRODUCT SELECTION GUIDE GOOD BETTER BEST

		tradeSELECT LUMEN & CCT			tradeSELECT			tradeselect Sutrement LUMEN & CCT			Mid-Spec Wrap			High-Spec Wrap			
	Length	2'	4'	8'	2'	4'	8'	2'	4'	8'	2'	4'	8'	2'	4'	8'	
	Ecngui	-	Yes	_	-	Yes	-	_	Yes	_	Yes	Yes	_	Yes	Yes	Yes	
	Width		5.3"		9"			9.7"			8.31"			8.5"			
	Continuous Row	ntinuous Row –				_			_			-			Yes		
	Lumens (maximum)	4095			4584			5880			7263			14,711			
	Efficacy (maximum LPW)		123		124			153			130			144			
	Life Rating	54,000 hours @ L70			54,000 hours @ L70			54,000 hours @ L70			60,000 hours @ L80			60,000 hours @ L80			
	CRI	80+			80+			80+			80+			80+			
FEATURES	сст	3500K, 4000K, 5000K			3500K, 4000K			3500K, 4000K, 5000K			3000K, 3500K, 4000K, 5000K			3000K, 3500K, 4000K, 5000K			
FEA	SpectraSync [™] Color Tuning Technology		_		-			_			-			Yes			
	SpectraSAFE™	-			-			-			-			Yes			
	Switchable Technology	Switchable Lumen & CCT			-			Switchable Lumen & CCT			_			-			
	Lens	Fr	osted Acry	ylic	Frosted Acrylic			Frosted Acrylic			Acrylic, Prismatic Overlay			Frosted Acrylic			
	Dimming	0–10V	/ Dimming	to 10%	0–10V Dimming to 10%			0–10V Dimming to 10%			0–10V Dimming to 1% and Dim to Dark			0–10V Dimming to 1% and Dim to Dark			
	Emergency Battery Pack		_					-			Yes			Yes			
	DLC® DesignLights Consortium		Standard		Standard			Premium			Standard			Standard			
	Buy America(n) Solutions	-			-			_			_			TAA FAR §52.225-11			
S :	Standalone Occupancy & Daylighting	-			_			_			-			Yes			
ROLE ROLE	NX Standalone Occupancy & Daylighting	-			_			-			-			Yes			
INTEGRATED CONTROLS	NX Networked Occupancy & Daylighting		-		-			-			-			-			
ŽΟ	PowerHUBB™		-						-			-			-		
USES	Applications		tion, Office Warehous		Education, Healthcare, Office, Warehouse				ation, Healt Retail, War		Education, Healthcare, Office, Warehouse			Education, Healthcare, Office, Retail, Warehouse			

DLC® (DesignLights Consortium) Qualified. Please refer to the DLC website for specific product qualifications at www.designlights.org



