


YCS341RL

by Burndy
Catalog ID: YCS341RL

Prop 65 Notice

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), 5-5/8 IN L



Product Details

General

Connector Type	Splice
Die Index	327
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	UNISPLICE™
UPC	781810015131
UPC 12 Digit	7818100151311

Dimensions

Dimension - L Length Overall mm	141 mm
Dimension - Length Overall inch	5.56 in
Dimension - Outside Diameter inch	1.13 in

Conductor Related

Conductor - ACSR Str Size	397.5 Kcmil, 336.4 kcmil
Conductor - AL Str Size	400 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)