

Products → Low Voltage Products and Systems → Connection Devices → Terminal Blocks Accessories
→ Jumper Bars

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | JB5-3 |
| Product ID: | 1SNK905303R0000 |
| EAN: | 3472599097568 |
| Catalog Description: | JB5-3 Jumper Bar - Orange |
| Long Description: | Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV). |

Ordering

| | |
|--------------------------------|----------|
| Color: | Orange |
| Minimum Order Quantity: | 50 piece |
| Customs Tariff Number: | 85369010 |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information: | 1SNK160027D0201 |
| Instructions and Manuals: | 1SNK160027C0201 |

Dimensions

| | |
|------------------------------------|---------|
| Product Net Width: | 5.2 mm |
| Product Net Height: | 13.4 mm |
| Product Net Length: | 26.8 mm |
| Product Net Depth / Length: | 26.8 mm |
| Product Net Weight: | 2 g |

Technical

| | |
|--|-------------------|
| Spacing: | 5.2 mm |
| Function: | Jumper Bars |
| Rated Current (I_n): | Main Circuit 32 A |
| Rated Short-time Withstand Current (I_{cw}): | for 1 s 480 A |
| Rated Voltage (U_r): | 1000 V |
| Rated Impulse Withstand Voltage (U_{imp}): | 8000 V |
| Dielectric Test Voltage: | 2200 V |

| | |
|------------------------------|--|
| Pollution Degree: | 3 |
| Power Loss: | 1 W |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material: | Polyamide |
| Suitable For: | ZDK2.5-22 ZDP2.5-11 ZDP2.5-22 ZDP2.5-D1 ZDP2.5-D2 ZDS4-22 ZK2.5 ZK2.5-3P ZK2.5-4P ZK2.5-CH-4P ZK2.5-D1 ZK2.5-D1-PE ZK2.5-D2 ZK2.5-D2-PE ZK2.5-D-CH ZK2.5-PE ZK2.5-PE-3P ZK2.5-PE-4P ZK2.5-S ZK2.5-S-4P ZK2.5-SF ZK2.5-SF-R ZK2.5-SP ZK2.5-SP-4P ZK2.5-S-R1 ZP2. |

Technical UL/CSA

| | |
|--|--------------------|
| Maximum Operating Voltage UL/CSA: | Main Circuit 600 V |
| Flammability According to UL94: | V0 |

Environmental

| | |
|--|---|
| Ambient Air Temperature: | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| Resistance to Vibrations acc. to IEC 60068-2-6: | Compliant |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Certificates and Declarations (Document Number)

| | |
|--------------------------|-----------------|
| ATEX Certificate: | 1SND162004A1708 |
| CB Certificate: | 1SND161017A0202 |

Instructions and Manuals: 1SNK160027C0201

RoHS Information: 1SND230499F0202

Classifications

Object Classification Code: X

E-nummer: 2925367

ETIM 4: EC000489 - Cross-connector for terminal block

ETIM 5: EC000489 - Cross-connector for terminal block

ETIM 6: EC000489 - Cross-connector for terminal block

Container Information

Package Level 1 Units: 50 piece

Package Level 1 Width: 50 mm

Package Level 1 Depth / Length: 117 mm

Package Level 1 Height: 50 mm

Package Level 1 Gross Weight: 0.1 kg

Package Level 1 EAN: 3472599097568

Package Level 2 Units: 1500 piece

Package Level 3 Units: 144000 piece

