

45° Liquidtight Connectors

With Copper Grounding Lug - Malleable Iron

Features

- Liquidtight, raintight, oiltight
- Copper lay-in grounding lug
- Insulated throat protects conductors from abrasion damage
- Zinc electro plated for excellent durability

Applications

- Use to connect liquidtight conduit and terminate an external bonding conductor that runs parallel to the conduit
- The NEC code specifies length limitations and that the bonding jumper must be parallel to the conduit
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

Standard Material


- Malleable iron
- Steel locknut
- Copper lug

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL 467 - UL 486A
- Fed. Spec: W-S-610E
- NEMA: GR 1-2017



Catalog Number	UPC Code	Conduit Size	Lug Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
231CSGR	03344	1/2"	14-4	5	50	17	1.36	1.50	2.51
232CSGR	03345	3/4"	14-4	5	50	24	1.61	1.73	2.70
233CSGR	03093	1"	14-4	2	20	16	1.89	2.11	3.05
234CSGR	03346	1-1/4"	14-4	2	20	24	2.39	2.56	3.65
235CSGR	03347	1-1/2"	14-4	2	20	26	2.62	2.77	4.01
236CSGR	03116	2"	14-4	2	20	37	3.24	3.38	4.64