

Job Name/Title: \_\_\_\_\_ Catalog Number \_\_\_\_\_  
Contractor: \_\_\_\_\_ Notes: \_\_\_\_\_

# Rigid Watertight Hubs

## Hot Dip Galvanized - Malleable Iron

### Features

- Flame-retardant insulated throat
- Male hub thread-NPT
- Female thread for Rigid conduit and IMC-NPT
- Recessed o-ring assures watertight and dust tight connections
- Type NHUB with insulated throat and bonding locknut is suitable for service entrance applications
- RoHS compliant

### Applications

- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes

### Standard Material


- Malleable iron

### Standard Finish

- Hot dip galvanized



Conforms to finish thickness ASTM  
A123/123M  
UL2239  
Fed. Spec. A-A-50553  
NEMA FB 1  
NEMA 2 3R, 4, 4X, 5, 12, 13



| Catalog Number | UPC   | Size   | Unit Carton | Ship Case | Weight/Case | A    | B    | C    |
|----------------|-------|--------|-------------|-----------|-------------|------|------|------|
| 201MHDG        | 00488 | 1/2"   | 25          | 250       | 58          | 1.54 | 1.36 | 1.09 |
| 202MHDG        | 00490 | 3/4"   | 10          | 100       | 34          | 1.77 | 1.50 | 1.30 |
| 203MHDG        | 00491 | 1"     | 10          | 100       | 52          | 2.15 | 1.77 | 1.59 |
| 204MHDG        | 00492 | 1-1/4" | 2           | 20        | 17          | 2.50 | 1.93 | 1.94 |
| 205MHDG        | 00494 | 1-1/2" | 2           | 20        | 21          | 3.01 | 1.97 | 2.20 |
| 206MHDG        | 00495 | 2"     | ---         | 10        | 15          | 3.35 | 2.05 | 2.68 |
| 207MHDG        | 00496 | 2-1/2" | ---         | 5         | 14          | 3.92 | 2.76 | 3.25 |
| 208MHDG        | 00497 | 3"     | ---         | 5         | 19          | 4.74 | 2.99 | 3.92 |
| 209MHDG        | 00498 | 3-1/2" | ---         | 5         | 24          | 5.39 | 3.09 | 4.46 |
| 210MHDG        | 00499 | 4"     | ---         | 1         | 8           | 5.91 | 3.31 | 4.82 |
| 210AMHDG       | 01862 | 5"     | ---         | 1         | 8           | 3.46 | 7.36 | 6.10 |
| 210BMHDG       | 01863 | 6"     | ---         | 1         | 11          | 3.62 | 8.39 | 7.25 |