

Rigid Conduit Bodies with Cover and Gasket

Threaded LL Type

Features

- Threaded LL type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber


Standard Finish

- Powder coat



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
LL1CG	21041	1/2"	1	6AWG	10	100	36	4.295	1.37	2.03
LL2CG	21051	3/4"	2	6AWG	10	50	23	5.09	1.625	2.33
LL3CG	21061	1"	3	6AWG	5	25	19	5.915	1.90	2.65
LL4CG	21071	1-1/4"	3	2AWG	2	10	15	7.894	2.77	3.385
LL5CG	21081	1-1/2"	3	2AWG	2	10	16	7.894	2.77	3.385
LL6CG	21091	2"	3	2/OAWG	1	5	14	10.134	3.335	3.81
LL7CG	21101	2-1/2"	3	4/OAWG	---	1	7	13	4.063	5.709
LL8CG	21111	3"	3	250MCM	---	1	7	12.75	4.682	5.506
LL9CG	21121	3-1/2"	3	350MCM	---	1	10	15.50	5.452	6.171
LL10CG	21131	4"	4	350MCM	---	1	10	15.50	5.452	6.171