

Rigid Watertight Hubs

With Bonding Screw - Aluminum

Features

- Flame-retardant insulated throat
- Rain, oil, and dust tight
- Oversized locknut protects against damage from vibrations and promotes positive grounding

Applications

- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes


Standard Material

- Aluminum



E195122

NEMA 2, 3R, 4, 4X, 5, 12, 13



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches		Max. Copper Wire Size UL#
						A	B	
201BAL	87158	1/2"	25	250	23	1.31	1.54	#8
202BAL	87159	3/4"	10	100	13	1.37	1.73	#8
203BAL	87160	1"	10	100	19	1.59	2.04	#8
204BAL	87161	1-1/4"	2	20	6	1.59	2.42	#8
205BAL	87162	1-1/2"	---	20	7	1.59	2.79	#8
206BAL	87163	2"	---	10	6	1.59	3.30	#8
207BAL	87164	2-1/2"	---	5	3	2.44	3.70	#6
208BAL	87165	3"	---	5	5	2.44	4.39	#6
209BAL	87166	3-1/2"	---	5	7	2.44	4.88	#6
210BAL	87167	4"	---	1	2	2.44	5.50	#4