

Grounding Locknuts

Steel

Features

- Tightens without deformation
- UL listed

Applications

- To connect externally threaded conduit connector to a threadless opening in a box or enclosure

Standard Material


- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	Thread Pitch Diameter
551	15250	1/2"	14	100	1000	30	1.15	.11	.787 - .797
552	15260	3/4"	14	100	1000	30	1.45	.115	.999 - 1.009
553	15270	1"	11-1/2	50	500	25	1.75	.14	1.25 - 1.26
554	15280	1-1/4"	11-1/2	50	500	30	2.10	.14	1.595 - 1.605
555	15290	1-1/2"	11-1/2	25	250	22	2.40	.14	1.837 - 1.847
556	15300	2"	11-1/2	20	200	28	2.95	.14	2.307 - 2.317
557	15310	2-1/2"	8	---	50	8	3.55	.185	2.777 - 2.788
558	15320	3"	8	---	50	14	3.55	.19	3.403 - 3.414
559	15330	3-1/2"	8	---	25	9	4.20	.19	3.892 - 3.904
560	15340	4"	8	---	25	10	4.75	.19	4.399 - 4.411