

Rigid Conduit Bodies

Threaded C Type

Features

- Threaded C type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat

Applicable Third Party Standards

- UL Standard: UL 514A
- Fed. Spec: W-C-586D
- NEMA: FB 1



Catalog Number	UPC	Size	Max. Number	Wire Size	Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size				A	B	C
C1	19900	1/2"	1	6 AWG	10	100	24	4.72	1.37	1.33
C2	19910	3/4"	2	6 AWG	10	50	21	5.57	1.625	1.54
C3	19920	1"	3	6 AWG	5	25	15	6.46	1.90	1.74
C4	19930	1-1/4"	3	2 AWG	2	10	15	8.528	2.77	2.49
C5	19940	1-1/2"	3	2 AWG	2	10	17	8.528	2.77	2.49
C6	19950	2"	3	2/0 AWG	1	5	13	10.831	3.335	3.10
C7	19960	2-1/2"	3	4/0 AWG	---	1	6	13.50	4.06	4.45
C8	19970	3"	3	250 MCM	---	1	6	13	4.685	4.45
C9	19980	3-1/2"	3	350 MCM	---	1	8	15.937	5.45	5.50
C10	19990	4"	4	350 MCM	---	1	8	15.937	5.45	5.50