

EMT and Rigid Combination Conduit Bodies with Covers and Gaskets

C Type

Features

- Combination C type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat



E195124
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
C1SSCG	83786	1/2"	1	6 AWG	10	100	30	5.35	1.31	1.31
C2SSCG	83787	3/4"	2	6 AWG	10	50	21	6	1.62	1.48
C3SSCG	83788	1"	3	6 AWG	5	25	17	7.06	1.88	1.75
C4SSCG	83789	1-1/4"	3	2 AWG	2	10	12	9.25	2.50	2.40
C5SSCG	83790	1-1/2"	3	2 AWG	2	10	15	9.25	2.67	2.40
C6SSCG	83791	2"	3	2/0 AWG	---	5	10	11.50	3.29	3.05