

Split Bolt Connectors

Solderless - For Copper & Copperweld Wire - Copper Alloy

Features

- Features copper pressure bar and hex style head
- Highly resistant to corrosion and cracking
- Provides high contact pressure between conductors
- UL 467 suitable for direct burial

Applications

- For copper to copper connections including copperweld wire

Standard Material

- Copper alloy



E155861
E195122

Catalog Number	UPC	Wire Size	Ship Case	Weight/ Case	Maximum Run to Minimum Tap Run	
690	17250	#10	100	2	16 STR	10 STR
691	17260	#8	100	3	8 STR 8 SOL	16 STR 16 SOL
692	17270	#6	100	5	6 SOL	16 SOL
693	17280	#6	100	6	6 STR 6 SOL	14 STR 14 SOL
694	17290	#4	50	8	4 STR 4 SOL	14 STR 14 SOL
695	17300	#2	50	11	2 STR 2 SOL	14 STR 14 SOL
696	17310	1/0	50	8	1/0 STR 1/0 SOL	14 STR 14 SOL
697	17320	2/0	25	7	2/0 STR 2/0 SOL	14 STR 14 SOL
698	17330	3/0	25	8	3/0 STR 3/0 SOL	8 STR 8 SOL
699	17340	4/0-250 MCM	5	10	250 STR	8 STR
700	17350	350 MCM	6	5	350 STR	1/0 STR
701	17360	500 MCM	6	5	500 STR	2/0 STR
702	17370	750 MCM	3	5	350 MCM	750 MCM
703	17380	1000 MCM	4	10	500 MCM	1000 MCM