

# Rigid Offset Nipples

## 3/4" Offset - Hot Dip Galvanized - Malleable Iron

### Features

- NPSM thread: Smooth inside surface to facilitate wire pulling free of damage

### Applications

- Indoor or outdoor use
- Use as an offset connector between two enclosures
- Offsets the axis of the raceways by 3/4"

### Standard Material

- Malleable iron


### Standard Finish

- Hot dip galvanized



E148716

Conforms to finish thickness ASTM  
A123/123M  
UL 514B  
RoHS  
Fed. Spec. A-A-50553  
NEMA FB 1



| Catalog Number  | UPC   | Size          | Unit Carton | Ship Case | Weight/Case | A    | Inches B | C   |
|-----------------|-------|---------------|-------------|-----------|-------------|------|----------|-----|
| <b>111MHDG</b>  | 83207 | <b>1/2"</b>   | 10          | 100       | 20          | 2.81 | 1.02     | .75 |
| <b>112MHDG</b>  | 83208 | <b>3/4"</b>   | 10          | 100       | 29          | 2.75 | 1.25     | .75 |
| <b>113MHDG</b>  | 83209 | <b>1"</b>     | 5           | 50        | 39          | 2.87 | 1.56     | .75 |
| <b>114MHDG</b>  | 83211 | <b>1-1/4"</b> | 5           | 50        | 32          | 3.13 | 2        | .75 |
| <b>115MHDG</b>  | 83213 | <b>1-1/2"</b> | 4           | 40        | 40          | 3.13 | 2.31     | .75 |
| <b>116MHDG</b>  | 83215 | <b>2"</b>     | 2           | 20        | 21          | 3.06 | 2.76     | .75 |
| <b>117MHDG</b>  | 83217 | <b>2-1/2"</b> | ---         | 2         | 3           | 3.97 | 3.26     | .75 |
| <b>118MHDG</b>  | 83219 | <b>3"</b>     | ---         | 2         | 5           | 4.43 | 3.81     | .75 |
| <b>119MHDG</b>  | 83221 | <b>3-1/2"</b> | ---         | 1         | 4           | 4.82 | 4.38     | .75 |
| <b>119AMHDG</b> | 86724 | <b>4"</b>     | ---         | 1         | 4           | 5.04 | 4.96     | .75 |