

Job Name/Title: _____ Catalog Number _____
Contractor: _____ Notes: _____

LED Linear Lighting

9W 2 Ft Direct-Fit LED Retrofit Frosted T8 with Internal Driver

Features

- Compatible with most electronic instant start, program start and emergency ballasts*
- Dimmable** Glass tube with PET coating is shatter resistant
- Extremely long life and energy efficient
- Contains no mercury
- Replaces 17W T8

Specs

- 120-277VAC
- 80 CRI
- 50,000 Average Rated Life
- 160° Beam angle and 240° light emitting area
- -20°C to 45°C Ambient temperature

Applications

- Office, retail, hospitality, warehouse

Frosted Glass
w/PET coating

24" Length

G13 Bi-pin Base



Catalog Number	Product Code	UPC Code	Color Temp	Lumens	Wattage	System Wattage	LPW	System LPW	Case Qty
L2T8E/835/9/F-70	77894	751338016842	3500K	1,300	9	11.5	144	113	1/25
L2T8E/840/9/F-70	77896	751338016859	4000K	1,350	9	11.5	150	117	1/25
L2T8E/850/9/F-70	77898	751338016866	5000K	1,400	9	11.5	156	122	1/25

Specifications are subject to change without prior notice.

* See ballast compatibility: www.topaz-usa.com/tools-resources/ballast-compatibility

**When used with dimmable fluorescent ballast