

Universal Strut Clamps

EMT and Rigid

Features

- For use with EMT/Rigid and IMC conduit
- All screws - 5/16" x 1-1/4" slotted hex head

Applications

- Use to support stationary pipe and tubing lines from strut channel

Standard Material


- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Screw Size	Ship Case	Weight/ Case	Inches	
						A	B
2101	41031	1/2"	1/4-20 x 1-1/4"	100	10	1.24	2.30
2102	41032	3/4"	1/4-20 x 1-1/4"	100	11	1.24	2.46
2103	41033	1"	1/4-20 x 1-1/4"	100	13	1.24	2.68
2104	41034	1-1/4"	1/4-20 x 1-1/4"	100	16	1.24	3.21
2105	41035	1-1/2"	5/16-18 x 1-1/2"	50	9	1.24	3.42
2106	41036	2"	5/16-18 x 1-1/2"	50	11	1.24	4
2107	41037	2-1/2"	5/16-18 x 1-3/4"	50	17	1.24	5
2108	41038	3"	5/16-18 x 1-3/4"	25	21	1.24	5.55
2109	41039	3-1/2"	5/16-18 x 1-3/4"	25	13	1.24	6
2110	41040	4"	5/16-18 x 1-3/4"	25	15	1.24	6.50