

# BX, Flex Connectors

## 90° - Squeeze Type with Insulated Throat - Malleable Iron

### Features

- Squeeze type with insulated throat

### Applications


- Indoor use only
- In a dry location, use to connect flexible metallic conduit, AC and steel MC cable to a steel outlet box or other metal enclosure

### Standard Material

- Malleable iron

### Standard Finish

- Zinc plated



| Catalog Number | UPC   | Conduit Size  | Unit Carton | Ship Case | Weight/Case | Inches |               |      |        |
|----------------|-------|---------------|-------------|-----------|-------------|--------|---------------|------|--------|
|                |       |               |             |           |             | A      | B (Min.-Max.) | C    | Screws |
| <b>101Mi</b>   | 10511 | <b>1/2"</b>   | 25          | 250       | 16          | 1.75   | .78 - .95     | .44  | 2      |
| <b>102Mi</b>   | 10521 | <b>3/4"</b>   | 10          | 100       | 30          | 1.81   | .91 - 1.02    | .44  | 2      |
| <b>103Mi</b>   | 10531 | <b>1"</b>     | 5           | 50        | 60          | 2.06   | 1.25 - 1.38   | .56  | 2      |
| <b>104Mi</b>   | 10541 | <b>1-1/4"</b> | 5           | 50        | 76          | 2.81   | 1.41 - 1.63   | .56  | 2      |
| <b>105Mi</b>   | 10551 | <b>1-1/2"</b> | ---         | 5         | 100         | 3.81   | 1.75 - 2      | .56  | 2      |
| <b>106Mi</b>   | 10561 | <b>2"</b>     | ---         | 5         | 200         | 4.75   | 2.19 - 2.44   | .69  | 2      |
| <b>107Mi</b>   | 10571 | <b>2-1/2"</b> | ---         | 5         | 320         | 6.25   | 2.75 - 3      | .88  | 4      |
| <b>108Mi</b>   | 10581 | <b>3"</b>     | ---         | 2         | 450         | 7.25   | 3.25 - 3.50   | 1    | 4      |
| <b>109Mi</b>   | 10591 | <b>3-1/2"</b> | ---         | 1         | 1400        | 10.25  | 3.70 - 4.16   | 1.25 | 4      |
| <b>110Mi</b>   | 10601 | <b>4"</b>     | ---         | 1         | 2400        | 13     | 4.11 - 4.56   | 1.25 | 4      |