

Job Name/Title:	_Catalog Number
Contractor:	Notes:

LED PLL Retrofit Lamp BALLAST COMPATIBLE UL TYPE A CFL REPLACEMENT





Retrofit Lamps Offer Labor and Utility Savings

Topaz's LED PLL Retrofit Lamps are a ballast compatible type A CFL replacement ideal for office, retail, and hospitality applications. This frosted glass lamp is suitable for damp locations and can be used in enclosed applications. With a 50,000 hour functional life, these high efficacy lamps are low maintenance saving labor and utility costs.

FEATURES

- Plug and play operation, no re-wiring required as these lamps are ballast compatible¹
- LED replacement for 40W Fluorescent 2G11 PLL Lamps
- Highly energy efficient with lamp efficacy up to 147 LPW
- Long Functional Life (L70) of 50,000 hours
- Suitable for dry and damp locations
- Suitable for enclosed fixtures²
- Frosted glass construction

SUGGESTED APPLICATIONS

- LED Replacement for 40W Fluorescent 2G11 PLL Lamps
- Office, retail, and hospitality
- Not for use in dimming applications or emergency ballasts















Job Name/Title:	_Catalog Number
Contractor:	Notes:

LED PLL Retrofit Lamp

BALLAST COMPATIBLE UL TYPE A CFL REPLACEMENT

GENERAL SPECIFICATIONS

Input Voltage, Frequency Hz: 120-277V, 50/60Hz

Power Factor, THD %: >0.9, <20%

Lamp Efficacy: Up to 147 Lumens Per Watt

Non-Dimmable

CRI: 80

Functional Life (L70): 50,000 hours

Location Rating: Damp

Ambient Operating Temperature: -4°F to 113°F

Suitable for Enclosed Fixtures²

Base Type: 2G11

ITEM SPECIFICATIONS / ORDER INFO

Catalog Number	Order Code	UPC	Lamp Lumens	Watts	ССТ	Beam Angle	DLC ID
LPLLE/17/835-39	70712	751338035041	2,350	17W	3500K	150°	PL2MYQCUQ3HT
LPLLE/17/840-39	70713	751338035058	2.500	17W	4000K	150°	PL48KDLW9262

NOMENCLATURE

Example: LPLLE/17/835

LPLLE = LED PLL Retrofit Lamp - Ballast Compatable, UL Type A / 17 = 17 Watts / 8 = 80 CRI 35 = 3500K

40 = 4000K

ENERGY SAVINGS

Catalog Number	LED Watts	Fluorescent Replacement Watts	Watts Saved	Yearly Savings	5 Year Savings
Based on 12 hours/day and 11¢/kwhr					
LPLLE/17/835-39	17W	40W	23W	\$11.08	\$55.40
LPLLE/17/840-39	17W	40W	23W	\$11.08	\$55.40

PRODUCT DIMENSIONS / LINE DRAWING

Catalog Number	(A)	(B)	Weight
LPLLE/17/835-39	22"	1.5"	.33 Lbs.
LPLLE/17/840-39	22"	1.5"	.33 Lbs.



NOTES:

Specifications subject to change without prior notice. Replacement wattage shown depends on application and fixture.

This device complies with Part 18 of the FCC Rules. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.

WARNING: Some products included in this specification sheet may be subject to the warning requirements of California's Proposition 65. Please refer to your product packaging for more information.

Revised February 2020

¹ Refer to ballast compatibility list on www.topaz-usa.com.

² Suitable for enclosed fixtures provided the ambient temperature inside fixture does not exceed 113° F.