

Rigid Locknuts

Steel

Features

- Tightens without deformation

Applications


- To connect externally threaded conduit or connector to a threadless opening in a box or enclosure

Standard Material

- Steel

Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	Thread Pitch Diameter
281	12300	1/2"	14	100	2000	20	1.15	.11	.787 - .797
282	12310	3/4"	14	100	1000	20	1.45	.115	.999 - 1.009
283	12320	1"	11-1/2	100	1000	30	1.75	.14	1.25 - 1.26
284	12330	1-1/4"	11-1/2	50	500	20	2.10	.14	1.595 - 1.605
285	12340	1-1/2"	11-1/2	50	500	30	2.40	.14	1.837 - 1.847
286	12350	2"	11-1/2	25	250	20	2.95	.14	2.307 - 2.317
287	12360	2-1/2"	8	---	50	6	3.55	.185	2.777 - 2.788
288	12370	3"	8	---	50	9	3.55	.19	3.403 - 3.414
289	12380	3-1/2"	8	---	25	6	4.20	.19	3.892 - 3.904
290	12390	4"	8	---	25	7	4.75	.19	4.399 - 4.411
290A	12400	5"	8	---	10	5	6.67	.38	5.488 - 5.50
290B	12410	6"	8	---	10	8	7.93	.40	6.545 - 6.557