

EMT and Rigid Combination Conduit Bodies with Covers and Gaskets

LR Type

Features

- Combination LR type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber


Standard Finish

- Powder coat



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	Inches B	C
			Max. Number	Max. Size						
LR1SSCG	83780	1/2"	1	6 AWG	10	100	30	4.56	1.31	2.06
LR2SSCG	83781	3/4"	2	6 AWG	10	50	20	5.31	1.62	2.23
LR3SSCG	83782	1"	3	6 AWG	5	25	16	6.25	1.88	2.50
LR4SSCG	83783	1-1/4"	3	2 AWG	2	10	12	8.22	2.50	3.40
LR5SSCG	83784	1-1/2"	3	2 AWG	2	10	12	8.22	2.67	3.48
LR6SSCG	83785	2"	3	2/0 AWG	---	5	9	10.48	3.29	4.07