

Rigid Connectors

Compression Type - Malleable Iron



Features

- Compression type connector
- Threadless
- Concrete tight

Applications

- Dry location only
- Use to join unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material


- Malleable iron

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
261M	85534	1/2"	20	200	13	1.50	1.50
262M	85535	3/4"	10	100	20	1.50	1.63
263M	85536	1"	5	50	36	1.687	2
264M	85537	1-1/4"	5	50	64	2	2.38
265M	85538	1-1/2"	---	12	92	2.0625	2.63
266M	85539	2"	---	12	117	2.25	3.31
267	12251	2-1/2"	---	5	14	3	3.75
268	12252	3"	---	3	13	3.125	4.25
269	12253	3-1/2"	---	2	13	3.187	4.75
270	12254	4"	---	2	13	3.437	5.312
270A	01493	5"	----	1	7	4.72	6.86
270B	01494	6"	---	1	8	5.04	8.14