

Job Name/Title: _____ Catalog Number _____
Contractor: _____ Notes: _____

Rigid Elbows

90° - Galvanized Steel

Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to Rigid conduit; bend enables directional changes in conduit

Standard Material


- Galvanized steel

Standard Finish

- Hot dip galvanized



1/2"-4" meet UL 6 and ANSI C80.1
Federal Specification WW-C-563



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End	(C) Offset
61	31030	1/2"	---	50	40	4	2.875	6.343
62	31040	3/4"	---	50	54	4.50	2.875	6.781
63	31050	1"	---	20	40	5.75	3	8.901
64	31060	1-1/4"	---	20	60	7.25	3.25	10.25
65	31070	1-1/2"	---	10	42	8.25	3.625	11.937
66	31080	2"	---	10	68	9.50	4.1875	14.031
67	31090	2-1/2"	1	50	650	10.50	5.25	16
68	31100	3"	1	35	630	13	5.8125	18.947
69	31110	3-1/2"	1	35	910	15	6.75	22.218
70	31120	4"	1	25	825	16	6.9375	23.437
70A	31127	5"	1	30	1350	24	11.125	36.156
70B	31128	6"	1	24	1152	30	12.4375	41.46