

Rigid Couplings

Three Piece Type - Hot Dip Galvanized - Malleable Iron

Features

- For threaded Rigid or IMC conduit
- Hot dip galvanized for superior protection against corrosion

Applications

- Use to join two lengths of threaded conduit or IMC when neither can be rotated

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness ASTM
A123/123M
UL 514B
RoHS
NEMA FB 1
Federal Spec. A-A-50553



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/ Case	Inches	
						A	B
851HDG	83190	1/2"	20	200	24	1.36	1.31
852HDG	83191	3/4"	10	100	30	1.41	1.57
853HDG	83192	1"	5	50	23	1.62	1.87
854HDG	83193	1-1/4"	5	50	55	1.83	2.28
855HDG	83194	1-1/2"	3	30	44	1.94	2.59
856HDG	83195	2"	2	20	44	2.23	3.14
857HDG	83197	2-1/2"	---	10	37	3.09	3.72
858HDG	83199	3"	---	5	20	3.19	4.37
859HDG	83201	3-1/2"	---	5	28	3.37	4.90
860HDG	83204	4"	---	2	18	3.45	5.44
860AHDG	83205	5"	---	1	9	4.38	7.00
860BHDG	83206	6"	---	1	11	4.38	8.25