

45° Liquidtight Connectors with Insulated Throat - Malleable Iron

Features

- Liquidtight, raintight, oiltight
- Suitable for wet locations
- Tapered threaded male hub NPT
- Insulated throat protects conductors from abrasion damage
- Compact slim diameter with small turning radius
- Zinc electro plated for excellent durability



Applications

- To secure, ground and seal liquidtight conduit to a box or enclosure
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I




Standard Material

- Malleable iron
- Steel locknut

Standard Finish

- Zinc plated



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	A	B	C
230S	11960	3/8" 1/2" KO	10	100	24	1.18	1.39	2.51
231S	11970	1/2"	10	100	28	1.36	1.50	2.51
232S	11980	3/4"	10	100	42	1.61	1.73	2.70
233S	11990	1"	5	50	32	1.89	2.11	3.05
234S	33550	1-1/4"	2	20	22	2.39	2.56	3.65
235S	33560	1-1/2"	2	20	32	2.62	2.77	4.01
236S	33570	2"	2	20	49	3.24	3.38	4.64
237S	33580	2-1/2"	---	1	5	3.89	4.68	6.46
238S	33590	3"	---	1	7	4.74	5.33	7.01
239S	33591	3-1/2"	---	1	10	5.31	5.81	7.33
240S	33610	4"	---	1	12	5.82	6.42	8.20