

BX, Flex Connectors

Straight - Squeeze Type - Zinc Die Cast

Features

- Squeeze type straight
- Available with insulated throat

Applications


- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- The 3/8" can also be used with steel and aluminum MC cable
- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" steel flexible conduit, #14/2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit

Standard Material

- Zinc die cast

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/ Case	Inches			
						A	B (Min.-Max.)	C	Screws
150	10990	3/8" 1/2" KO	50	500	35	1	.58-.61	.37	1
151	11000	1/2"	25	250	25	1.47	.74-.95	.40	1
152	11010	3/4"	25	250	32	1.58	.88-1.11	.40	1
153	11020	1"	10	100	20	1.75	1.14-1.38	.54	1
154	11030	1-1/4"	10	100	29	1.91	1.42-1.65	.64	1
155	11040	1-1/2"	5	50	20	2.09	1.68-1.94	.75	1
156	11050	2"	10	40	21	2.34	2.08-2.56	.74	1
157	11060	2-1/2"	---	10	9	2.81	2.85-3.25	.875	2
158	11070	3"	---	10	17	3.84	3.33-3.63	1.03	2
159	11080	3-1/2"	---	1	3	4.19	3.75-4.10	1.03	2
160	11090	4"	---	1	3	4.56	4.18-4.58	1.03	2