

Rigid Conduit Bodies

Threaded LR Type - Hot Dip Galvanized

Features

- Hot dip galvanized finish provides superior protection against severe environmental factors

Applications

- Compatible with all Form 5 & Form 35 series conduit bodies and covers
- Provides taps for branch conduit runs
- Enables 90 degree bends in conduit runs

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness ASTM
A123/123M
UL 514A and UL 514D
Fed. Spec. A-A-50563
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Internal Volume (in ³)	Ship Case	Weight/ Case	Inches		
			Max. Number	Max. Size				A	B	C
LR1MHDG	86633	1/2"	---	---	4.5	10	7	4.69	1.46	2.08
LR2MHDG	86634	3/4"	3	6 AWG	7.5	10	10	5.42	1.65	2.31
LR3MHDG	86635	1"	3	4 AWG	12.5	5	6	6.28	1.98	2.68
LR4MHDG	86636	1-1/4"	3	2 AWG	32.3	5	13	8.12	2.60	3.41
LR5MHDG	86637	1-1/2"	3	1/0 AWG	35.3	2	6	8.15	2.80	3.45
LR6MHDG	86638	2"	3	4/0 AWG	73	1	6	10.53	3.52	4.15
LR7MHDG	86639	2-1/2"	3	300 MCM	142	1	10	13.76	3.98	5.86
LR8MHDG	86640	3"	3	350 MCM	173	1	13	13.82	4.65	5.92
LR9MHDG	86641	3-1/2"	3	350 MCM	300	1	22	16.65	5.43	7.14
LR10MHDG	86642	4"	3	350 MCM	330	1	24	16.65	5.74	7.19