

EMT and Rigid Combination Conduit Bodies with Covers and Gaskets

T Type

Features

- Combination T type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat



E195124
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
T1SSCG	83792	1/2"	1	6 AWG	10	100	35	5.35	1.31	2.02
T2SSCG	83793	3/4"	2	6 AWG	10	50	23	6	1.62	2.22
T3SSCG	83794	1"	3	6 AWG	5	25	18	7.06	1.88	2.56
T4SSCG	83795	1-1/4"	3	2 AWG	2	10	13	7.25	2.50	3.50
T5SSCG	83796	1-1/2"	3	2 AWG	2	10	11	9.25	2.67	3.50
T6SSCG	83797	2"	3	2/0 AWG	---	5	10	11.50	3.29	4.25