

# Insulating Plastic Bushings

## 105°C Flame Retardant

### Features


- Rated flame retardant to 105°C

### Applications

- Indoor or outdoor use
- Use with locknut to terminate threaded Rigid or IMC conduit to an outlet box

### Standard Material

- Thermoplastic



| Catalog Number | UPC   | Size          | Unit Carton | Ship Case | Weight/Case | Inches |     |
|----------------|-------|---------------|-------------|-----------|-------------|--------|-----|
|                |       |               |             |           |             | A      | B   |
| <b>831</b>     | 18450 | <b>1/2"</b>   | 100         | 1000      | 5           | 1.06   | .43 |
| <b>832</b>     | 18460 | <b>3/4"</b>   | 100         | 1000      | 7           | 1.31   | .43 |
| <b>833</b>     | 18470 | <b>1"</b>     | 50          | 500       | 7           | 1.59   | .48 |
| <b>834</b>     | 18480 | <b>1-1/4"</b> | 25          | 250       | 4           | 1.96   | .56 |
| <b>835</b>     | 18490 | <b>1-1/2"</b> | 25          | 250       | 5           | 2.18   | .56 |
| <b>836</b>     | 18500 | <b>2"</b>     | 20          | 200       | 6           | 2.68   | .59 |
| <b>837</b>     | 18510 | <b>2-1/2"</b> | ---         | 50        | 2           | 3.25   | .72 |
| <b>838</b>     | 18520 | <b>3"</b>     | ---         | 25        | 2           | 3.87   | .75 |
| <b>839</b>     | 18530 | <b>3-1/2"</b> | ---         | 25        | 2           | 4.37   | .77 |
| <b>840</b>     | 18540 | <b>4"</b>     | ---         | 10        | 1           | 5      | .77 |
| <b>840A</b>    | 18550 | <b>5"</b>     | ---         | 10        | 1           | 6.25   | 1   |
| <b>840B</b>    | 18560 | <b>6"</b>     | ---         | 10        | 2           | 7.50   | 1   |