

LED Mini-Reflectors

5W and 8W Dimmable LED MR16

Features

- Long life—up to 10 times longer than traditional incandescent/halogen lamps
- Advanced thermal management for cool-to-touch operation
- Dimmable to 10% for additional energy savings and ambiance control*
- RoHS compliant and mercury free
- Use with electronic low voltage power supply**

Specs

- 70 Lumens Per Watt (LPW)
- 12V
- 80 CRI
- 25,000 Average Rated Life
- -20°C Minimum start temp
- 35° Beam angle

Applications

- Track lighting, displays & accent lighting



Catalog Number	Order Code	UPC	CCT	Wattage	Lumens	CBCP	Input Current	ETL Listed	Case Qty
LM16/5/830/FL/D	74140	751338015500	3000K	5W	350	906cd	600mA	Y	1/24
LM16/5/840/FL/D	74141	751338015517	4000K	5W	350	906cd	600mA	Y	1/24
LM16/5/850/FL/D	74142	751338015555	5000K	5W	350	906cd	600mA	Y	1/24
LM16/8/830/FL/D	74143	751338015562	3000K	8W	560	1,315cd	900mA	Y	1/24
LM16/8/840/FL/D	74144	751338015586	4000K	8W	560	1,315cd	900mA	Y	1/24
LM16/8/850/FL/D	74145	751338015593	5000K	8W	560	1,315cd	900mA	Y	1/24

Not for sale in residential new construction in California.
 Specifications are subject to change without prior notice.
 Not suitable for use in enclosed fixtures.

*Compatible with most electronic low voltage dimmers, such as: Lutron SELV-300 (300P), CTELV-300P (303P), MAELV-600, Leviton IPE04, 6615. Visit www.topaz-usa.com/led-dimmer-compatibility for up-to-date dimmer compatibility information

**Recommended for use with electronic low volt power supplies; not recommended for use with magnetic low voltage power supply
 Must adhere to minimum load/max load power supply requirements.