

# BX, Flex Connectors

## Straight - Squeeze Type with Insulated Throat - Zinc Die Cast

### Features


- Squeeze type straight with insulated throat

### Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- Suitable for: 1/2" steel flexible conduit, #14/2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit

### Standard Material

- Zinc die cast



| Catalog Number | UPC   | Conduit Size  | Unit Carton | Ship Case | Weight/ Case | Inches |               |     |        |
|----------------|-------|---------------|-------------|-----------|--------------|--------|---------------|-----|--------|
|                |       |               |             |           |              | A      | B (Min.-Max.) | C   | Screws |
| <b>151i</b>    | 11001 | <b>1/2"</b>   | 25          | 250       | 25           | 1.47   | .74-.95       | .40 | 1      |
| <b>152i</b>    | 11011 | <b>3/4"</b>   | 25          | 250       | 32           | 1.58   | .88-1.11      | .40 | 1      |
| <b>153i</b>    | 11021 | <b>1"</b>     | 10          | 100       | 20           | 1.75   | 1.14-1.38     | .54 | 1      |
| <b>154i</b>    | 11031 | <b>1-1/4"</b> | 10          | 100       | 29           | 1.91   | 1.42-1.65     | .64 | 1      |
| <b>155i</b>    | 11041 | <b>1-1/2"</b> | 5           | 50        | 20           | 2.09   | 1.68-1.94     | .75 | 1      |
| <b>156i</b>    | 11051 | <b>2"</b>     | 10          | 40        | 21           | 2.34   | 2.08-2.56     | .74 | 1      |