

Rigid Straps

One Hole - Hot Dip Galvanized Malleable Iron

Features

- Hot dip galvanized for added durability and corrosion protection

Applications

- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

Standard Material

- Malleable iron


Standard Finish

- Hot dip galvanized



E174011

Conforms to finish
thickness ASTM A123/123M
UL 2239
Fed. Spec. A-A-50553
NEMA FB 1



Catalog Number	UPC	Size	Hole Size	Unit Carton	Ship Case	Weight/Case	Inches A	B	C
561HDG	86589	1/2"	.31	100	1000	40	1.98	.67	.97
562HDG	86590	3/4"	.31	50	500	25	2.37	.76	1.10
563HDG	86591	1"	.31	25	250	20	2.90	.82	1.44
564HDG	86592	1-1/4"	.43	20	250	25	3.12	.82	1.77
565HDG	86593	1-1/2"	.45	10	200	32	3.90	1.05	2.06
566HDG	86594	2"	.55	---	100	36	4.77	1.36	2.59
567HDG	86595	2-1/2"	.57	---	25	17	5.45	1.36	3.05
568HDG	86596	3"	.57	---	25	25	6.74	1.54	3.77
569HDG	86597	3-1/2"	.69	---	25	38	7.72	1.91	4.24
570HDG	86598	4"	.71	---	10	23	8.13	2.07	4.98
570AHDG	86599	5"	.96	---	10	34	10.94	2.55	6.22
570BHDG	86600	6"	1.18	---	10	40	12.71	2.91	7.45