

Job Name/Title: _____ Catalog Number _____
Contractor: _____ Notes: _____

Rigid Bushings

Insulated - 105°C Thermoplastic Liner - Zinc

Features

- Liner is rated flame retardant to 105°C

Applications


- Indoor or outdoor use
- Use with locknut to terminate Rigid or IMC conduit to an outlet box
- Plastic liner prevents damage to wire insulation

Standard Material

- Zinc
- Plastic insulator

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
311	12730	1/2"	100	1000	30	1.053	.394
312	12740	3/4"	50	500	20	1.327	.394
313	12750	1"	50	500	40	1.584	.477
314	12760	1-1/4"	25	250	25	1.952	.503
315	12770	1-1/2"	25	250	27	2.201	.522
316	12780	2"	10	100	17	2.693	.564
317	12790	2-1/2"	---	50	20	3.235	.866
318	12800	3"	---	25	12	3.855	.866
319	12810	3-1/2"	---	25	14	4.359	.866
320	12820	4"	---	10	6	5.011	.866